

<b>RAMPS AND RAMP JUNCTIONS WORKSHEET</b>									
<b>General Information</b>					<b>Site Information</b>				
Analyst	AL				Freeway/Dir of Travel	I-75 EB			
Agency or Company	AIM ENGINEERING				Junction	SR 29 EB ON			
Date Performed	3/16/2012				Jurisdiction				
Analysis Time Period	PM				Analysis Year	2019 WHITE			
Project Description									
<b>Inputs</b>									
Upstream Adj Ramp		Number of Lanes, N			2 ✓			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Acceleration Lane Length, L <sub>A</sub>			560			<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Deceleration Lane Length L <sub>D</sub>						<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L <sub>up</sub> = ft		Freeway Volume, V <sub>F</sub>			1247 ✓			L <sub>down</sub> = ft	
V <sub>u</sub> = veh/h		Ramp Volume, V <sub>R</sub>			271 ✓			V <sub>D</sub> = veh/h	
		Freeway Free-Flow Speed, S <sub>FF</sub>			70.0 ✓				
		Ramp Free-Flow Speed, S <sub>FR</sub>			35.0				
<b>Conversion to pc/h Under Base Conditions</b>									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	1247	0.90 ✓	Level	6	0	0.971	0.90 ✓	1586	
Ramp	271	0.90 ✓	Level	22	0	0.901	0.90 ✓	371	
UpStream									
DownStream									
<b>Merge Areas</b>					<b>Diverge Areas</b>				
<b>Estimation of v<sub>12</sub></b>					<b>Estimation of v<sub>12</sub></b>				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L <sub>EQ</sub> =					L <sub>EQ</sub> =				
P <sub>FM</sub> = 1.000 using Equation (Exhibit 13-6)					P <sub>FD</sub> = using Equation (Exhibit 13-7)				
V <sub>12</sub> = 1586 pc/h					V <sub>12</sub> = pc/h				
V <sub>3</sub> or V <sub>av34</sub> = 0 pc/h (Equation 13-14 or 13-17)					V <sub>3</sub> or V <sub>av34</sub> = pc/h (Equation 13-14 or 13-17)				
Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No				
Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No				
If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)				
<b>Capacity Checks</b>					<b>Capacity Checks</b>				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>	1957	Exhibit 13-8		No	V <sub>F</sub>		Exhibit 13-8		
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>		Exhibit 13-8		
					V <sub>R</sub>		Exhibit 13-10		
<b>Flow Entering Merge Influence Area</b>					<b>Flow Entering Diverge Influence Area</b>				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>	1957	Exhibit 13-8	4600:All	No	V <sub>12</sub>		Exhibit 13-8		
<b>Level of Service Determination (if not F)</b>					<b>Level of Service Determination (if not F)</b>				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$				
D <sub>R</sub> = 17.1 (pc/mi/ln)					D <sub>R</sub> = (pc/mi/ln)				
LOS = B (Exhibit 13-2)					LOS = (Exhibit 13-2)				

<b>RAMPS AND RAMP JUNCTIONS WORKSHEET</b>									
<b>General Information</b>					<b>Site Information</b>				
Analyst	AL				Freeway/Dir of Travel	I-75 WB			
Agency or Company	AIM ENGINEERING				Junction	SR 29 OFF RAMP			
Date Performed	3/8/2012				Jurisdiction				
Analysis Time Period	PM				Analysis Year	2019 WHITE			
Project Description									
<b>Inputs</b>									
Upstream Adj Ramp		Number of Lanes, N			2 ✓			Downstream Adj Ramp	
<input type="checkbox"/> Yes	<input type="checkbox"/> On	Acceleration Lane Length, L <sub>A</sub>						<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No	<input type="checkbox"/> Off	Deceleration Lane Length L <sub>D</sub>			215			<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L <sub>up</sub> =	ft	Freeway Volume, V <sub>F</sub>			1193 ✓			L <sub>down</sub> =	
V <sub>u</sub> =	veh/h	Ramp Volume, V <sub>R</sub>			213 ✓			ft	
		Freeway Free-Flow Speed, S <sub>FF</sub>			70.0 ✓			V <sub>D</sub> =	
		Ramp Free-Flow Speed, S <sub>FR</sub>			45.0 ✓			veh/h	
<b>Conversion to pc/h Under Base Conditions</b>									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	1193	0.90 ✓	Level	6	0	0.971	0.90 ✓	1517	
Ramp	213	0.90	Level	22	0	0.901	0.90	292	
UpStream									
DownStream									
<b>Merge Areas</b>					<b>Diverge Areas</b>				
<b>Estimation of v<sub>12</sub></b>					<b>Estimation of v<sub>12</sub></b>				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L <sub>EQ</sub> = P <sub>FM</sub> = using Equation (Exhibit 13-6) V <sub>12</sub> = pc/h V <sub>3</sub> or V <sub>av34</sub> pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L <sub>EQ</sub> = P <sub>FD</sub> = 1.000 using Equation (Exhibit 13-7) V <sub>12</sub> = 1517 pc/h V <sub>3</sub> or V <sub>av34</sub> 0 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)				
<b>Capacity Checks</b>					<b>Capacity Checks</b>				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>		Exhibit 13-8			V <sub>F</sub>	1517	Exhibit 13-8	4800	No
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>	1225	Exhibit 13-8	4800	No
					V <sub>R</sub>	292	Exhibit 13-10	2100	No
<b>Flow Entering Merge Influence Area</b>					<b>Flow Entering Diverge Influence Area</b>				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>		Exhibit 13-8			V <sub>12</sub>	1517	Exhibit 13-8	4400:All	No
<b>Level of Service Determination (if not F)</b>					<b>Level of Service Determination (if not F)</b>				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> = 15.4 (pc/mi/ln) LOS = B (Exhibit 13-2)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	AL	Freeway/Dir of Travel	I-75 WB						
Agency or Company	AIM ENGINEERING	Junction	SR 29 WB ON						
Date Performed	3/16/2012	Jurisdiction							
Analysis Time Period	PM	Analysis Year	2019 WHITE						
Project Description									
Inputs									
Upstream Adj Ramp	Number of Lanes, N		2 ✓		Downstream Adj Ramp				
<input type="checkbox"/> Yes <input type="checkbox"/> On	Acceleration Lane Length, L <sub>A</sub>		415		<input type="checkbox"/> Yes <input type="checkbox"/> On				
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	Deceleration Lane Length L <sub>D</sub>				<input checked="" type="checkbox"/> No <input type="checkbox"/> Off				
L <sub>up</sub> = ft	Freeway Volume, V <sub>F</sub>		980 ✓		L <sub>down</sub> = ft				
V <sub>u</sub> = veh/h	Ramp Volume, V <sub>R</sub>		325 ✓		V <sub>D</sub> = veh/h				
	Freeway Free-Flow Speed, S <sub>FF</sub>		70.0 ✓						
	Ramp Free-Flow Speed, S <sub>FR</sub>		35.0						
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	980	0.90 ✓	Level	6	0	0.971	0.90 ✓	1246	
Ramp	325	0.90 ✓	Level	22	0	0.901	0.90 ✓	445	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v <sub>12</sub>					Estimation of v <sub>12</sub>				
$V_{12} = V_F (P_{FM})$ L <sub>EQ</sub> = (Equation 13-6 or 13-7) P <sub>FM</sub> = 1.000 using Equation (Exhibit 13-6) V <sub>12</sub> = 1246 pc/h V <sub>3</sub> or V <sub>av34</sub> = 0 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ L <sub>EQ</sub> = (Equation 13-12 or 13-13) P <sub>FD</sub> = using Equation (Exhibit 13-7) V <sub>12</sub> = pc/h V <sub>3</sub> or V <sub>av34</sub> = pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>	1691	Exhibit 13-8		No	V <sub>F</sub>		Exhibit 13-8		
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>		Exhibit 13-8		
					V <sub>R</sub>		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>	1691	Exhibit 13-8		No	V <sub>12</sub>		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> = 15.9 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> = (pc/mi/ln) LOS = (Exhibit 13-2)				

Phone: Fax:  
E-mail:

-----Diverge Analysis-----

Analyst: GSR  
Agency/Co.: AIM ENGINEERING  
Date performed: 4/4/2012  
Analysis time period: PM  
Freeway/Dir of Travel: I-75 EB  
Junction: SR 951 OFF RAMP  
Jurisdiction:  
Analysis Year: 2019 WHITE  
Description:

-----Freeway Data-----

Type of analysis	Diverge	
Number of lanes in freeway	2	
Free-flow speed on freeway	70.0	mph
Volume on freeway	3339	vph

-----Off Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	2	
Free-Flow speed on ramp	45.0	mph
Volume on ramp	1909	vph
Length of first accel/decel lane	500	ft
Length of second accel/decel lane	0	ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	No	
Volume on adjacent ramp		vph
Position of adjacent ramp		
Type of adjacent ramp		
Distance to adjacent ramp		ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	3339	1909		vph
Peak-hour factor, PHF	0.90	0.90		
Peak 15-min volume, v15	928	530		v
Trucks and buses	6	6		%
Recreational vehicles	0	0		%
Terrain type:	Level	Level		
Grade	0.00	%	0.00	%
Length	0.00	mi	0.00	mi
Trucks and buses PCE, ET	1.5*	1.5		
Recreational vehicle PCE, ER	1.2	1.2		



Heavy vehicle adjustment, fHV	0.971	0.971	
Driver population factor, fP	1.00	1.00	
Flow rate, vp	3821	2185	pcph

----- Estimation of V12 Diverge Areas -----

L = (Equation 25-8 or 25-9)  
 EQ  
 P = 1.000 Using Equation 0  
 FD  
 $v_{12} = v_R + (v_F - v_R) P = 3821$  pc/h  
 12 R F R FD

----- Capacity Checks -----

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	3821	4800	No
$v_{FO} = v_F - v_R$	1636	4800	No
$v_R$	2185	4100	No
$v_{3 \text{ or } av34}$	0 pc/h	(Equation 25-15 or 25-16)	
Is $v_{3 \text{ or } av34} > 2700$ pc/h?		No	
Is $v_{3 \text{ or } av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} =$		(Equation 25-18)	

----- Flow Entering Diverge Influence Area -----

	Actual	Max Desirable	Violation?
$v_{12}$	3821	4600	No

----- Level of Service Determination (if not F) -----

Density,  $D = 4.252 + 0.0086 v_{12} - 0.009 L_D = 28.1$  pc/mi/ln  
 Level of service for ramp-freeway junction areas of influence D

----- Speed Estimation -----

Intermediate speed variable,	D = 0.495	
Space mean speed in ramp influence area,	S = 56.1	mph
Space mean speed in outer lanes,	S = N/A	mph
Space mean speed for all vehicles,	S = 56.1	mph

<b>RAMPS AND RAMP JUNCTIONS WORKSHEET</b>									
<b>General Information</b>					<b>Site Information</b>				
Analyst	AL				Freeway/Dir of Travel	I-75 EB			
Agency or Company	AIM ENGINEERING				Junction	SR 951 EB ON			
Date Performed	3/16/2012				Jurisdiction				
Analysis Time Period	PM				Analysis Year	2019 WHITE			
Project Description									
<b>Inputs</b>									
Upstream Adj Ramp		Number of Lanes, N			2			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Acceleration Lane Length, L <sub>A</sub>			465			<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Deceleration Lane Length L <sub>D</sub>						<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L <sub>up</sub> =        ft		Freeway Volume, V <sub>F</sub>			1430			L <sub>down</sub> =        ft	
V <sub>u</sub> =        veh/h		Ramp Volume, V <sub>R</sub>			230			V <sub>D</sub> =        veh/h	
		Freeway Free-Flow Speed, S <sub>FF</sub>			70.0				
		Ramp Free-Flow Speed, S <sub>FR</sub>			35.0				
<b>Conversion to pc/h Under Base Conditions</b>									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	1430	0.90	Level	6	0	0.971	0.90	1818	
Ramp	230	0.90	Level	6	0	0.971	0.90	292	
UpStream									
DownStream									
<b>Merge Areas</b>					<b>Diverge Areas</b>				
<b>Estimation of v<sub>12</sub></b>					<b>Estimation of v<sub>12</sub></b>				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L <sub>EQ</sub> = P <sub>FM</sub> = 1.000 using Equation (Exhibit 13-6) V <sub>12</sub> = 1818 pc/h V <sub>3</sub> or V <sub>av34</sub> = 0 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> =        pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L <sub>EQ</sub> = P <sub>FD</sub> = using Equation (Exhibit 13-7) V <sub>12</sub> = pc/h V <sub>3</sub> or V <sub>av34</sub> = pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> =        pc/h (Equation 13-16, 13-18, or 13-19)				
<b>Capacity Checks</b>					<b>Capacity Checks</b>				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>	2110	Exhibit 13-8		No	V <sub>F</sub>		Exhibit 13-8		
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>		Exhibit 13-8		
					V <sub>R</sub>		Exhibit 13-10		
<b>Flow Entering Merge Influence Area</b>					<b>Flow Entering Diverge Influence Area</b>				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>	2110	Exhibit 13-8		No	V <sub>12</sub>		Exhibit 13-8		
<b>Level of Service Determination (if not F)</b>					<b>Level of Service Determination (if not F)</b>				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> = 18.9 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> = (pc/mi/ln) LOS = (Exhibit 13-2)				

<b>RAMPS AND RAMP JUNCTIONS WORKSHEET</b>									
<b>General Information</b>					<b>Site Information</b>				
Analyst	AL				Freeway/Dir of Travel	I-75 WB			
Agency or Company	AIM ENGINEERING				Junction	SR 951 OFF RAMP			
Date Performed	3/8/2012				Jurisdiction				
Analysis Time Period	PM				Analysis Year	2019 WHITE			
Project Description									
<b>Inputs</b>									
Upstream Adj Ramp		Number of Lanes, N			2			Downstream Adj Ramp	
<input type="checkbox"/> Yes	<input type="checkbox"/> On	Acceleration Lane Length, L <sub>A</sub>						<input type="checkbox"/> Yes	<input type="checkbox"/> On
<input checked="" type="checkbox"/> No	<input type="checkbox"/> Off	Deceleration Lane Length L <sub>D</sub>			220			<input checked="" type="checkbox"/> No	<input type="checkbox"/> Off
L <sub>up</sub> =	ft	Freeway Volume, V <sub>F</sub>			1305			L <sub>down</sub> =	ft
V <sub>u</sub> =	veh/h	Ramp Volume, V <sub>R</sub>			181			V <sub>D</sub> =	veh/h
		Freeway Free-Flow Speed, S <sub>FF</sub>			70.0				
		Ramp Free-Flow Speed, S <sub>FR</sub>			45.0				
<b>Conversion to pc/h Under Base Conditions</b>									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	1305	0.90	Level	6	0	0.971	0.90	1659	
Ramp	181	0.90	Level	6	0	0.971	0.90	230	
UpStream									
DownStream									
<b>Merge Areas</b>					<b>Diverge Areas</b>				
<b>Estimation of v<sub>12</sub></b>					<b>Estimation of v<sub>12</sub></b>				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L <sub>EQ</sub> =					L <sub>EQ</sub> =				
P <sub>FM</sub> = using Equation (Exhibit 13-6)					P <sub>FD</sub> = 1.000 using Equation (Exhibit 13-7)				
V <sub>12</sub> = pc/h					V <sub>12</sub> = 1659 pc/h				
V <sub>3</sub> or V <sub>av34</sub> pc/h (Equation 13-14 or 13-17)					V <sub>3</sub> or V <sub>av34</sub> 0 pc/h (Equation 13-14 or 13-17)				
Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)				
<b>Capacity Checks</b>					<b>Capacity Checks</b>				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>		Exhibit 13-8			V <sub>F</sub>	1659	Exhibit 13-8	4800	No
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>	1429	Exhibit 13-8	4800	No
					V <sub>R</sub>	230	Exhibit 13-10	2100	No
<b>Flow Entering Merge Influence Area</b>					<b>Flow Entering Diverge Influence Area</b>				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>		Exhibit 13-8			V <sub>12</sub>	1659	Exhibit 13-8	4400:All	No
<b>Level of Service Determination (if not F)</b>					<b>Level of Service Determination (if not F)</b>				
D <sub>R</sub> = 5.475 + 0.00734 v <sub>R</sub> + 0.0078 V <sub>12</sub> - 0.00627 L <sub>A</sub>					D <sub>R</sub> = 4.252 + 0.0086 V <sub>12</sub> - 0.009 L <sub>D</sub>				
D <sub>R</sub> = (pc/mi/ln)					D <sub>R</sub> = 16.5 (pc/mi/ln)				
LOS = (Exhibit 13-2)					LOS = B (Exhibit 13-2)				


<b>RAMPS AND RAMP JUNCTIONS WORKSHEET</b>									
<b>General Information</b>					<b>Site Information</b>				
Analyst	AL				Freeway/Dir of Travel	I-75 WB			
Agency or Company	AIM ENGINEERING				Junction	SR 951 WB ON			
Date Performed	3/16/2012				Jurisdiction				
Analysis Time Period	PM				Analysis Year	2019 WHITE			
Project Description									
<b>Inputs</b>									
Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L <sub>up</sub> =        ft V <sub>u</sub> =        veh/h	Number of Lanes, N                    2 ✓ Acceleration Lane Length, L <sub>A</sub> 385 Deceleration Lane Length L <sub>D</sub> Freeway Volume, V <sub>F</sub> 1124 ✓ Ramp Volume, V <sub>R</sub> 1500 ✓ Freeway Free-Flow Speed, S <sub>FF</sub> 70.0 ✓ Ramp Free-Flow Speed, S <sub>FR</sub> 35.0				Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L <sub>down</sub> =        ft V <sub>D</sub> =        veh/h				
<b>Conversion to pc/h Under Base Conditions</b>									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	1124	0.90 ✓	Level	6	0	0.971	1.00 ✓	1286	
Ramp	1500	0.90 ✓	Level	6	0	0.971	1.00 ✓	1717	
UpStream									
DownStream									
<b>Merge Areas</b>					<b>Diverge Areas</b>				
<b>Estimation of v<sub>12</sub></b>					<b>Estimation of v<sub>12</sub></b>				
$V_{12} = V_F (P_{FM})$ L <sub>EQ</sub> =                    (Equation 13-6 or 13-7) P <sub>FM</sub> =                    1.000 using Equation (Exhibit 13-6) V <sub>12</sub> =                    1286 pc/h V <sub>3</sub> or V <sub>av34</sub> 0 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> =            pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ L <sub>EQ</sub> =                    (Equation 13-12 or 13-13) P <sub>FD</sub> =                    using Equation (Exhibit 13-7) V <sub>12</sub> =                    pc/h V <sub>3</sub> or V <sub>av34</sub> pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> =            pc/h (Equation 13-16, 13-18, or 13-19)				
<b>Capacity Checks</b>					<b>Capacity Checks</b>				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>	3003	Exhibit 13-8		No	V <sub>F</sub>		Exhibit 13-8		
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>		Exhibit 13-8		
					V <sub>R</sub>		Exhibit 13-10		
<b>Flow Entering Merge Influence Area</b>					<b>Flow Entering Diverge Influence Area</b>				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>	3003	Exhibit 13-8		No	V <sub>12</sub>		Exhibit 13-8		
<b>Level of Service Determination (if not F)</b>					<b>Level of Service Determination (if not F)</b>				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> =    25.7 (pc/mi/ln) LOS =    C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> =    (pc/mi/ln) LOS =    (Exhibit 13-2)				

<b>RAMPS AND RAMP JUNCTIONS WORKSHEET</b>									
<b>General Information</b>					<b>Site Information</b>				
Analyst	AL				Freeway/Dir of Travel	I-75 NB			
Agency or Company	AIM ENGINEERING				Junction	GGP NB OFF RAMP			
Date Performed	3/8/2012				Jurisdiction				
Analysis Time Period	PM				Analysis Year	2019 WHITE			
Project Description									
<b>Inputs</b>									
Upstream Adj Ramp		Number of Lanes, N			3 ✓			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Acceleration Lane Length, L <sub>A</sub>						<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Deceleration Lane Length L <sub>D</sub>			310			<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L <sub>up</sub> =      ft		Freeway Volume, V <sub>F</sub>			2624 ✓			L <sub>down</sub> =      ft	
V <sub>u</sub> =      veh/h		Ramp Volume, V <sub>R</sub>			350 ✓			V <sub>D</sub> =      veh/h	
		Freeway Free-Flow Speed, S <sub>FF</sub>			70.0 ✓				
		Ramp Free-Flow Speed, S <sub>FR</sub>			45.0 ✓				
<b>Conversion to pc/h Under Base Conditions</b>									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	2624	0.90 ✓	Level	6	0	0.971	1.00 ✓	3003	
Ramp	350	0.90 ✓	Level	6	0	0.971	1.00 ✓	401	
UpStream									
DownStream									
<b>Merge Areas</b>					<b>Diverge Areas</b>				
<b>Estimation of v<sub>12</sub></b>					<b>Estimation of v<sub>12</sub></b>				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L <sub>EQ</sub> = P <sub>FM</sub> = using Equation (Exhibit 13-6) V <sub>12</sub> = pc/h V <sub>3</sub> or V <sub>av34</sub> pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L <sub>EQ</sub> = P <sub>FD</sub> = 0.666 using Equation (Exhibit 13-7) V <sub>12</sub> = 2135 pc/h V <sub>3</sub> or V <sub>av34</sub> 868 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)				
<b>Capacity Checks</b>					<b>Capacity Checks</b>				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>		Exhibit 13-8			V <sub>F</sub>	3003	Exhibit 13-8	7200	No
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>	2602	Exhibit 13-8	7200	No
					V <sub>R</sub>	401	Exhibit 13-10	2100	No
<b>Flow Entering Merge Influence Area</b>					<b>Flow Entering Diverge Influence Area</b>				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>		Exhibit 13-8			V <sub>12</sub>	2135	Exhibit 13-8	4400:All	No
<b>Level of Service Determination (if not F)</b>					<b>Level of Service Determination (if not F)</b>				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> = 19.8 (pc/mi/ln) LOS = B (Exhibit 13-2)				

BASIC FREEWAY SEGMENTS WORKSHEET																								
		<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Application</th> <th>Input</th> <th>Output</th> </tr> </thead> <tbody> <tr> <td>Operational (LOS)</td> <td>FFS, N, v<sub>p</sub></td> <td>LOS, S, D</td> </tr> <tr> <td>Design (N)</td> <td>FFS, LOS, v<sub>p</sub></td> <td>N, S, D</td> </tr> <tr> <td>Design (v<sub>p</sub>)</td> <td>FFS, LOS, N</td> <td>v<sub>p</sub>, S, D</td> </tr> <tr> <td>Planning (LOS)</td> <td>FFS, N, AADT</td> <td>LOS, S, D</td> </tr> <tr> <td>Planning (N)</td> <td>FFS, LOS, AADT</td> <td>N, S, D</td> </tr> <tr> <td>Planning (v<sub>p</sub>)</td> <td>FFS, LOS, N</td> <td>v<sub>p</sub>, S, D</td> </tr> </tbody> </table>		Application	Input	Output	Operational (LOS)	FFS, N, v <sub>p</sub>	LOS, S, D	Design (N)	FFS, LOS, v <sub>p</sub>	N, S, D	Design (v <sub>p</sub> )	FFS, LOS, N	v <sub>p</sub> , S, D	Planning (LOS)	FFS, N, AADT	LOS, S, D	Planning (N)	FFS, LOS, AADT	N, S, D	Planning (v <sub>p</sub> )	FFS, LOS, N	v <sub>p</sub> , S, D
Application	Input	Output																						
Operational (LOS)	FFS, N, v <sub>p</sub>	LOS, S, D																						
Design (N)	FFS, LOS, v <sub>p</sub>	N, S, D																						
Design (v <sub>p</sub> )	FFS, LOS, N	v <sub>p</sub> , S, D																						
Planning (LOS)	FFS, N, AADT	LOS, S, D																						
Planning (N)	FFS, LOS, AADT	N, S, D																						
Planning (v <sub>p</sub> )	FFS, LOS, N	v <sub>p</sub> , S, D																						
<b>General Information</b>		<b>Site Information</b>																						
Analyst	GSR	Highway/Direction of Travel	I-75																					
Agency or Company	AIM ENGINEERING	From/To	BTWN NB GG PKW ON/OFF-RAMPS																					
Date Performed	3/26/2012	Jurisdiction																						
Analysis Time Period	PM	Analysis Year	2019 WHITE LAKE EXT																					
Project Description EVERGLADES IJR																								
<input checked="" type="checkbox"/> Oper.(LOS)		<input type="checkbox"/> Des.(N)																						
<input type="checkbox"/> Planning Data																								
<b>Flow Inputs</b>																								
Volume, V	2274	veh/h	Peak-Hour Factor, PHF																					
AADT		veh/day	%Trucks and Buses, P <sub>T</sub>																					
Peak-Hr Prop. of AADT, K			%RVs, P <sub>R</sub>																					
Peak-Hr Direction Prop., D			General Terrain:																					
DDHV = AADT x K x D		veh/h	Grade % Length																					
Driver type adjustment	1.00		Up/Down %																					
<b>Calculate Flow Adjustments</b>																								
f <sub>p</sub>	1.00	E <sub>R</sub>	1.2																					
E <sub>T</sub>	1.5	f <sub>HV</sub> = 1/[1+P <sub>T</sub> (E <sub>T</sub> - 1) + P <sub>R</sub> (E <sub>R</sub> - 1)]	0.971																					
<b>Speed Inputs</b>		<b>Calc Speed Adj and FFS</b>																						
Lane Width	12.0	ft	f <sub>LW</sub>																					
Rt-Shoulder Lat. Clearance	6.0	ft	f <sub>LC</sub>																					
Interchange Density	0.50	l/mi	f <sub>ID</sub>																					
Number of Lanes, N	2		f <sub>N</sub>																					
FFS (measured)		mi/h	FFS																					
Base free-flow Speed, BFFS	75.0	mi/h																						
<b>LOS and Performance Measures</b>		<b>Design (N)</b>																						
<u>Operational (LOS)</u>		<u>Design (N)</u>																						
v <sub>p</sub> = (V or DDHV) / (PHF x N x f <sub>HV</sub> x f <sub>p</sub> )	1301	pc/h/ln	Design LOS																					
S	70.5	mi/h	v <sub>p</sub> = (V or DDHV) / (PHF x N x f <sub>HV</sub> x f <sub>p</sub> )																					
D = v <sub>p</sub> / S	18.5	pc/mi/ln	S																					
LOS	C		D = v <sub>p</sub> / S																					
			Required Number of Lanes, N																					
<b>Glossary</b>		<b>Factor Location</b>																						
N - Number of lanes	S - Speed	E <sub>R</sub> - Exhibits 23-8, 23-10	f <sub>LW</sub> - Exhibit 23-4																					
V - Hourly volume	D - Density	E <sub>T</sub> - Exhibits 23-8, 23-10, 23-11	f <sub>LC</sub> - Exhibit 23-5																					
v <sub>p</sub> - Flow rate	FFS - Free-flow speed	f <sub>p</sub> - Page 23-12	f <sub>N</sub> - Exhibit 23-6																					
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v <sub>p</sub> - Exhibits 23-2, 23-3	f <sub>ID</sub> - Exhibit 23-7																					
DDHV - Directional design hour volume																								



**BASIC FREEWAY SEGMENTS WORKSHEET**



General Information		Site Information	
Analyst	AL	Highway/Direction of Travel	I-75
Agency or Company	AIM ENGINEERING	From/To	N OF GG PKWY_NB
Date Performed	3/6/2012	Jurisdiction	
Analysis Time Period	PM	Analysis Year	2019 WHITE ALT

Project Description EVERGLADES IJR  
 Oper.(LOS)       Des.(N)       Planning Data

Flow Inputs			
Volume, V	4353	veh/h	Peak-Hour Factor, PHF 0.90
AADT		veh/day	%Trucks and Buses, P <sub>T</sub> 6
Peak-Hr Prop. of AADT, K			%RVs, P <sub>R</sub> 0
Peak-Hr Direction Prop, D			General Terrain: Level
DDHV = AADT x K x D		veh/h	Grade % Length mi
Driver type adjustment	1.00		Up/Down %

Calculate Flow Adjustments			
f <sub>p</sub>	1.00	E <sub>R</sub>	1.2
E <sub>T</sub>	1.5	f <sub>HV</sub> = 1/[1+P <sub>T</sub> (E <sub>T</sub> - 1) + P <sub>R</sub> (E <sub>R</sub> - 1)]	0.971

Speed Inputs		Calc Speed Adj and FFS	
Lane Width	12.0 ft	f <sub>LW</sub>	0.0 mi/h
Rt-Shoulder Lat. Clearance	6.0 ft	f <sub>LC</sub>	0.0 mi/h
Interchange Density	0.50 l/mi	f <sub>ID</sub>	0.0 mi/h
Number of Lanes, N	3	f <sub>N</sub>	3.0 mi/h
FFS (measured)		FFS	72.0 mi/h
Base free-flow Speed, BFFS	75.0 mi/h		

LOS and Performance Measures		Design (N)	
<u>Operational (LOS)</u>		<u>Design (N)</u>	
v <sub>p</sub> = (V or DDHV) / (PHF x N x f <sub>HV</sub> x f <sub>p</sub> )	1661 pc/h/ln	Design LOS	
S	70.7 mi/h	v <sub>p</sub> = (V or DDHV) / (PHF x N x f <sub>HV</sub> x f <sub>p</sub> )	pc/h
D = v <sub>p</sub> / S	23.5 pc/mi/ln	S	mi/h
LOS	C	D = v <sub>p</sub> / S	pc/mi/ln
		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	E <sub>R</sub> - Exhibits 23-8, 23-10	f <sub>LW</sub> - Exhibit 23-4
V - Hourly volume	D - Density	E <sub>T</sub> - Exhibits 23-8, 23-10, 23-11	f <sub>LC</sub> - Exhibit 23-5
v <sub>p</sub> - Flow rate	FFS - Free-flow speed	f <sub>p</sub> - Page 23-12	f <sub>N</sub> - Exhibit 23-6
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, v <sub>p</sub> - Exhibits 23-2, 23-3	f <sub>ID</sub> - Exhibit 23-7
DDHV - Directional design hour volume			

BASIC FREEWAY SEGMENTS WORKSHEET																								
		<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Application</th> <th>Input</th> <th>Output</th> </tr> </thead> <tbody> <tr> <td>Operational (LOS)</td> <td>FFS, N, <math>v_p</math></td> <td>LOS, S, D</td> </tr> <tr> <td>Design (N)</td> <td>FFS, LOS, <math>v_p</math></td> <td>N, S, D</td> </tr> <tr> <td>Design (<math>v_p</math>)</td> <td>FFS, LOS, N</td> <td><math>v_p</math>, S, D</td> </tr> <tr> <td>Planning (LOS)</td> <td>FFS, N, AADT</td> <td>LOS, S, D</td> </tr> <tr> <td>Planning (H)</td> <td>FFS, LOS, AADT</td> <td>N, S, D</td> </tr> <tr> <td>Planning (<math>v_p</math>)</td> <td>FFS, LOS, N</td> <td><math>v_p</math>, S, D</td> </tr> </tbody> </table>		Application	Input	Output	Operational (LOS)	FFS, N, $v_p$	LOS, S, D	Design (N)	FFS, LOS, $v_p$	N, S, D	Design ( $v_p$ )	FFS, LOS, N	$v_p$ , S, D	Planning (LOS)	FFS, N, AADT	LOS, S, D	Planning (H)	FFS, LOS, AADT	N, S, D	Planning ( $v_p$ )	FFS, LOS, N	$v_p$ , S, D
Application	Input	Output																						
Operational (LOS)	FFS, N, $v_p$	LOS, S, D																						
Design (N)	FFS, LOS, $v_p$	N, S, D																						
Design ( $v_p$ )	FFS, LOS, N	$v_p$ , S, D																						
Planning (LOS)	FFS, N, AADT	LOS, S, D																						
Planning (H)	FFS, LOS, AADT	N, S, D																						
Planning ( $v_p$ )	FFS, LOS, N	$v_p$ , S, D																						
<b>General Information</b>		<b>Site Information</b>																						
Analyst	AL	Highway/Direction of Travel	I-75																					
Agency or Company	AIM ENGINEERING	From/To	N OF GG PKWY_SB																					
Date Performed	3/6/2012	Jurisdiction																						
Analysis Time Period	PM	Analysis Year	2019 WHITE ALT																					
Project Description EVERGLADES IJR																								
<input type="checkbox"/> Oper.(LOS)		<input type="checkbox"/> Des.(N)																						
<input type="checkbox"/> Planning Data																								
<b>Flow Inputs</b>																								
Volume, V	4444	veh/h	Peak-Hour Factor, PHF																					
AADT		veh/day	%Trucks and Buses, $P_T$																					
Peak-Hr Prop. of AADT, K			%RVs, $P_R$																					
Peak-Hr Direction Prop, D			General Terrain:																					
DDHV = AADT x K x D		veh/h	Grade % Length																					
Driver type adjustment	1.00		Up/Down %																					
<b>Calculate Flow Adjustments</b>																								
$f_p$	1.00	$E_R$	1.2																					
$E_T$	1.5	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	0.971																					
<b>Speed Inputs</b>		<b>Calc Speed Adj and FFS</b>																						
Lane Width	12.0	ft	$f_{LW}$																					
Rt-Shoulder Lat. Clearance	6.0	ft	$f_{LC}$																					
Interchange Density	0.50	l/mi	$f_{ID}$																					
Number of Lanes, N	3		$f_N$																					
FFS (measured)		mi/h	FFS																					
Base free-flow Speed, BFFS	75.0	mi/h																						
<b>LOS and Performance Measures</b>		<b>Design (N)</b>																						
<u>Operational (LOS)</u>		<u>Design (N)</u>																						
$v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$	1695	pc/h/ln	Design LOS																					
S	70.4	mi/h	$v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$																					
$D = v_p / S$	24.1	pc/mi/ln	S																					
LOS	C		$D = v_p / S$																					
		Required Number of Lanes, N																						
<b>Glossary</b>		<b>Factor Location</b>																						
N - Number of lanes	S - Speed	$E_R$ - Exhibits 23-8, 23-10	$f_{LW}$ - Exhibit 23-4																					
V - Hourly volume	D - Density	$E_T$ - Exhibits 23-8, 23-10, 23-11	$f_{LC}$ - Exhibit 23-5																					
$v_p$ - Flow rate	FFS - Free-flow speed	$f_p$ - Page 23-12	$f_N$ - Exhibit 23-6																					
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, $v_p$ - Exhibits 23-2, 23-3	$f_{ID}$ - Exhibit 23-7																					
DDHV - Directional design hour volume																								

BASIC FREEWAY SEGMENTS WORKSHEET																										
<p>The graph plots Average Passenger-Car Speed (mi/h) on the y-axis (30 to 80) against Flow Rate (pc/h/ln) on the x-axis (0 to 2400). It shows several dashed curves representing different Free-Flow Speeds (FFS): 75 mi/h, 70 mi/h, 65 mi/h, 60 mi/h, and 55 mi/h. Dotted lines represent density levels: 11 pc/mi/ln, 19 pc/mi/ln, 25 pc/mi/ln, 35 pc/mi/ln, and 45 pc/mi/ln. Points A, B, C, D, and E are marked on the graph, corresponding to different flow and speed conditions.</p>			<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Application</th> <th style="text-align: left;">Input</th> <th style="text-align: left;">Output</th> </tr> </thead> <tbody> <tr> <td>Operational (LOS)</td> <td>FFS, N, v<sub>p</sub></td> <td>LOS, S, D</td> </tr> <tr> <td>Design (N)</td> <td>FFS, LOS, v<sub>p</sub></td> <td>N, S, D</td> </tr> <tr> <td>Design (v<sub>p</sub>)</td> <td>FFS, LOS, N</td> <td>v<sub>p</sub>, S, D</td> </tr> <tr> <td>Planning (LOS)</td> <td>FFS, N, AADT</td> <td>LOS, S, D</td> </tr> <tr> <td>Planning (N)</td> <td>FFS, LOS, AADT</td> <td>N, S, D</td> </tr> <tr> <td>Planning (v<sub>p</sub>)</td> <td>FFS, LOS, N</td> <td>v<sub>p</sub>, S, D</td> </tr> </tbody> </table>			Application	Input	Output	Operational (LOS)	FFS, N, v <sub>p</sub>	LOS, S, D	Design (N)	FFS, LOS, v <sub>p</sub>	N, S, D	Design (v <sub>p</sub> )	FFS, LOS, N	v <sub>p</sub> , S, D	Planning (LOS)	FFS, N, AADT	LOS, S, D	Planning (N)	FFS, LOS, AADT	N, S, D	Planning (v <sub>p</sub> )	FFS, LOS, N	v <sub>p</sub> , S, D
Application	Input	Output																								
Operational (LOS)	FFS, N, v <sub>p</sub>	LOS, S, D																								
Design (N)	FFS, LOS, v <sub>p</sub>	N, S, D																								
Design (v <sub>p</sub> )	FFS, LOS, N	v <sub>p</sub> , S, D																								
Planning (LOS)	FFS, N, AADT	LOS, S, D																								
Planning (N)	FFS, LOS, AADT	N, S, D																								
Planning (v <sub>p</sub> )	FFS, LOS, N	v <sub>p</sub> , S, D																								
<b>General Information</b>			<b>Site Information</b>																							
Analyst	GSR	Highway/Direction of Travel	I-75																							
Agency or Company	AIM ENGINEERING	From/To	BTWN SB GG PKW ON-OFF-RAMPS																							
Date Performed	3/26/2012	Jurisdiction																								
Analysis Time Period	PM	Analysis Year	2019 WHITE LAKE EXT																							
Project Description EVERGLADES IJR																										
<input type="checkbox"/> Oper.(LOS)		<input type="checkbox"/> Des.(N)		<input type="checkbox"/> Planning Data																						
<b>Flow Inputs</b>																										
Volume, V	2893	veh/h	Peak-Hour Factor, PHF	0.90																						
AADT		veh/day	%Trucks and Buses, P <sub>T</sub>	6																						
Peak-Hr Prop. of AADT, K			%RVs, P <sub>R</sub>	0																						
Peak-Hr Direction Prop, D			General Terrain:	Level																						
DDHV = AADT x K x D		veh/h	Grade % Length	mi																						
Driver type adjustment	1.00		Up/Down %																							
<b>Calculate Flow Adjustments</b>																										
f <sub>p</sub>	1.00		E <sub>R</sub>	1.2																						
E <sub>T</sub>	1.5		f <sub>HV</sub> = 1/[1+P <sub>T</sub> (E <sub>T</sub> - 1) + P <sub>R</sub> (E <sub>R</sub> - 1)]	0.971																						
<b>Speed Inputs</b>			<b>Calc Speed Adj and FFS</b>																							
Lane Width	12.0	ft	f <sub>LW</sub>	0.0	mi/h																					
Rt-Shoulder Lat. Clearance	6.0	ft	f <sub>LC</sub>	0.0	mi/h																					
Interchange Density	0.50	l/mi	f <sub>ID</sub>	0.0	mi/h																					
Number of Lanes, N	2		f <sub>N</sub>	4.5	mi/h																					
FFS (measured)		mi/h	FFS	70.5	mi/h																					
Base free-flow Speed, BFFS	75.0	mi/h																								
<b>LOS and Performance Measures</b>			<b>Design (N)</b>																							
<u>Operational (LOS)</u>			<u>Design (N)</u>																							
v <sub>p</sub> = (V or DDHV) / (PHF x N x f <sub>HV</sub> x f <sub>p</sub> )	1655	pc/h/ln	Design LOS																							
S	69.5	mi/h	v <sub>p</sub> = (V or DDHV) / (PHF x N x f <sub>HV</sub> x f <sub>p</sub> )	pc/h																						
D = v <sub>p</sub> / S	23.8	pc/mi/ln	S	mi/h																						
LOS	C		D = v <sub>p</sub> / S	pc/mi/ln																						
			Required Number of Lanes, N																							
<b>Glossary</b>			<b>Factor Location</b>																							
N - Number of lanes	S - Speed		E <sub>R</sub> - Exhibits 23-8, 23-10	f <sub>LW</sub> - Exhibit 23-4																						
V - Hourly volume	D - Density		E <sub>T</sub> - Exhibits 23-8, 23-10, 23-11	f <sub>LC</sub> - Exhibit 23-5																						
v <sub>p</sub> - Flow rate	FFS - Free-flow speed		f <sub>p</sub> - Page 23-12	f <sub>N</sub> - Exhibit 23-6																						
LOS - Level of service	BFFS - Base free-flow speed		LOS, S, FFS, v <sub>p</sub> - Exhibits 23-2, 23-3	f <sub>ID</sub> - Exhibit 23-7																						
DDHV - Directional design hour volume																										

<b>RAMPS AND RAMP JUNCTIONS WORKSHEET</b>									
<b>General Information</b>					<b>Site Information</b>				
Analyst	AL				Freeway/Dir of Travel	I-75 SB			
Agency or Company	AIM ENGINEERING				Junction	GOLDEN GATE PKWY SB ON			
Date Performed	3/16/2012				Jurisdiction				
Analysis Time Period	PM				Analysis Year	2019 WHITE			
Project Description									
<b>Inputs</b>									
Upstream Adj Ramp		Number of Lanes, N			3 ✓			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Acceleration Lane Length, L <sub>A</sub>			550			<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Deceleration Lane Length L <sub>D</sub>						<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L <sub>up</sub> = ft		Freeway Volume, V <sub>F</sub>			2893 ✓			L <sub>down</sub> = ft	
V <sub>u</sub> = veh/h		Ramp Volume, V <sub>R</sub>			446 ✓			V <sub>D</sub> = veh/h	
		Freeway Free-Flow Speed, S <sub>FF</sub>			70.0 ✓				
		Ramp Free-Flow Speed, S <sub>FR</sub>			35.0				
<b>Conversion to pc/h Under Base Conditions</b>									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	2893	0.90 ✓	Level	6	0	0.971	1.00 ✓	3311	
Ramp	446	0.90	Level	6	0	0.971	1.00 ✓	510	
UpStream									
DownStream									
<b>Merge Areas</b>					<b>Diverge Areas</b>				
<b>Estimation of v<sub>12</sub></b>					<b>Estimation of v<sub>12</sub></b>				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L <sub>EQ</sub> = P <sub>FM</sub> = 0.593 using Equation (Exhibit 13-6) V <sub>12</sub> = 1963 pc/h V <sub>3</sub> or V <sub>av34</sub> = 1348 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L <sub>EQ</sub> = P <sub>FD</sub> = using Equation (Exhibit 13-7) V <sub>12</sub> = pc/h V <sub>3</sub> or V <sub>av34</sub> = pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)				
<b>Capacity Checks</b>					<b>Capacity Checks</b>				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>	3821	Exhibit 13-8		No	V <sub>F</sub>		Exhibit 13-8		
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>		Exhibit 13-8		
					V <sub>R</sub>		Exhibit 13-10		
<b>Flow Entering Merge Influence Area</b>					<b>Flow Entering Diverge Influence Area</b>				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>	2473	Exhibit 13-8 4600:All		No	V <sub>12</sub>		Exhibit 13-8		
<b>Level of Service Determination (if not F)</b>					<b>Level of Service Determination (if not F)</b>				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> = 21.1 (pc/mi/ln)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> = (pc/mi/ln)				
LOS = C (Exhibit 13-2)									



RAMPS AND RAMP JUNCTIONS WORKSHEET																																																																					
General Information					Site Information																																																																
Analyst	AL	Freeway/Dir of Travel	I-75 EB																																																																		
Agency or Company	AIM ENGINEERING	Junction	SR 29 OFF RAMP																																																																		
Date Performed	3/8/2012	Jurisdiction																																																																			
Analysis Time Period	AM	Analysis Year	2019 EVERGLADES																																																																		
Project Description																																																																					
Inputs																																																																					
Upstream Adj Ramp		Number of Lanes, N					Downstream Adj Ramp																																																														
<input type="checkbox"/> Yes <input type="checkbox"/> On		Acceleration Lane Length, $L_A$					<input type="checkbox"/> Yes <input type="checkbox"/> On																																																														
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Deceleration Lane Length $L_D$					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off																																																														
$L_{up} =$	ft	Freeway Volume, $V_F$					$L_{down} =$																																																														
$V_u =$	veh/h	Ramp Volume, $V_R$					ft																																																														
		Freeway Free-Flow Speed, $S_{FF}$					$V_D =$																																																														
		Ramp Free-Flow Speed, $S_{FR}$					veh/h																																																														
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th colspan="10">Conversion to pc/h Under Base Conditions</th> </tr> <tr> <th>(pc/h)</th> <th>V (Veh/hr)</th> <th>PHF</th> <th>Terrain</th> <th>%Truck</th> <th>%Rv</th> <th><math>f_{HV}</math></th> <th><math>f_p</math></th> <th colspan="2"><math>v = V/PHF \times f_{HV} \times f_p</math></th> </tr> </thead> <tbody> <tr> <td>Freeway</td> <td>1376</td> <td>0.90</td> <td>Level</td> <td>6</td> <td>0</td> <td>0.971</td> <td>0.90</td> <td colspan="2">1750</td> </tr> <tr> <td>Ramp</td> <td>340</td> <td>0.90</td> <td>Level</td> <td>22</td> <td>0</td> <td>0.901</td> <td>0.90</td> <td colspan="2">466</td> </tr> <tr> <td>UpStream</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="2"></td> </tr> <tr> <td>DownStream</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="2"></td> </tr> </tbody> </table>										Conversion to pc/h Under Base Conditions										(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	$f_{HV}$	$f_p$	$v = V/PHF \times f_{HV} \times f_p$		Freeway	1376	0.90	Level	6	0	0.971	0.90	1750		Ramp	340	0.90	Level	22	0	0.901	0.90	466		UpStream										DownStream									
Conversion to pc/h Under Base Conditions																																																																					
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	$f_{HV}$	$f_p$	$v = V/PHF \times f_{HV} \times f_p$																																																													
Freeway	1376	0.90	Level	6	0	0.971	0.90	1750																																																													
Ramp	340	0.90	Level	22	0	0.901	0.90	466																																																													
UpStream																																																																					
DownStream																																																																					
Merge Areas					Diverge Areas																																																																
Estimation of $v_{12}$					Estimation of $v_{12}$																																																																
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) $L_{EQ} =$ using Equation (Exhibit 13-6) $P_{FM} =$ pc/h $V_{12} =$ pc/h (Equation 13-14 or 13-17) $V_3$ or $V_{av34}$ pc/h (Equation 13-14 or 13-17) Is $V_3$ or $V_{av34} > 2,700$ pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is $V_3$ or $V_{av34} > 1.5 * V_{12}/2$ <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, $V_{12a} =$ pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) $L_{EQ} =$ 1.000 using Equation (Exhibit 13-7) $P_{FD} =$ 1750 pc/h $V_{12} =$ 0 pc/h (Equation 13-14 or 13-17) $V_3$ or $V_{av34}$ 0 pc/h (Equation 13-14 or 13-17) Is $V_3$ or $V_{av34} > 2,700$ pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is $V_3$ or $V_{av34} > 1.5 * V_{12}/2$ <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, $V_{12a} =$ pc/h (Equation 13-16, 13-18, or 13-19)																																																																
Capacity Checks					Capacity Checks																																																																
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Actual</th> <th>Capacity</th> <th colspan="2">LOS F?</th> </tr> </thead> <tbody> <tr> <td><math>V_{FO}</math></td> <td></td> <td>Exhibit 13-8</td> <td></td> <td></td> </tr> </tbody> </table>						Actual	Capacity	LOS F?		$V_{FO}$		Exhibit 13-8			<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Actual</th> <th>Capacity</th> <th colspan="2">LOS F?</th> </tr> </thead> <tbody> <tr> <td><math>V_F</math></td> <td>1750</td> <td>Exhibit 13-8</td> <td>4800</td> <td>No</td> </tr> <tr> <td><math>V_{FO} = V_F - V_R</math></td> <td>1284</td> <td>Exhibit 13-8</td> <td>4800</td> <td>No</td> </tr> <tr> <td><math>V_R</math></td> <td>466</td> <td>Exhibit 13-10</td> <td>2100</td> <td>No</td> </tr> </tbody> </table>						Actual	Capacity	LOS F?		$V_F$	1750	Exhibit 13-8	4800	No	$V_{FO} = V_F - V_R$	1284	Exhibit 13-8	4800	No	$V_R$	466	Exhibit 13-10	2100	No																														
	Actual	Capacity	LOS F?																																																																		
$V_{FO}$		Exhibit 13-8																																																																			
	Actual	Capacity	LOS F?																																																																		
$V_F$	1750	Exhibit 13-8	4800	No																																																																	
$V_{FO} = V_F - V_R$	1284	Exhibit 13-8	4800	No																																																																	
$V_R$	466	Exhibit 13-10	2100	No																																																																	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area																																																																
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Actual</th> <th>Max Desirable</th> <th colspan="2">Violation?</th> </tr> </thead> <tbody> <tr> <td><math>V_{R12}</math></td> <td></td> <td>Exhibit 13-8</td> <td></td> <td></td> </tr> </tbody> </table>						Actual	Max Desirable	Violation?		$V_{R12}$		Exhibit 13-8			<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Actual</th> <th>Max Desirable</th> <th colspan="2">Violation?</th> </tr> </thead> <tbody> <tr> <td><math>V_{12}</math></td> <td>1750</td> <td>Exhibit 13-8</td> <td>4400:All</td> <td>No</td> </tr> </tbody> </table>						Actual	Max Desirable	Violation?		$V_{12}$	1750	Exhibit 13-8	4400:All	No																																								
	Actual	Max Desirable	Violation?																																																																		
$V_{R12}$		Exhibit 13-8																																																																			
	Actual	Max Desirable	Violation?																																																																		
$V_{12}$	1750	Exhibit 13-8	4400:All	No																																																																	
Level of Service Determination (if not F)					Level of Service Determination (if not F)																																																																
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ $D_R =$ (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ $D_R =$ 17.5 (pc/mi/ln) LOS = B (Exhibit 13-2)																																																																



<b>RAMPS AND RAMP JUNCTIONS WORKSHEET</b>									
<b>General Information</b>					<b>Site Information</b>				
Analyst	AL	Freeway/Dir of Travel	I-75 EB		Agency or Company	AIM ENGINEERING	Junction	SR 29 EB ON	
Date Performed	3/16/2012	Jurisdiction			Analysis Time Period	AM	Analysis Year	2019 EVERGLADES	
Project Description									
<b>Inputs</b>									
Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L <sub>up</sub> =      ft V <sub>u</sub> =      veh/h	Number of Lanes, N Acceleration Lane Length, L <sub>A</sub> Deceleration Lane Length L <sub>D</sub> Freeway Volume, V <sub>F</sub> Ramp Volume, V <sub>R</sub> Freeway Free-Flow Speed, S <sub>FF</sub> Ramp Free-Flow Speed, S <sub>FR</sub>	2 ✓ 560  1036 ✓ 157 ✓ 70.0 ✓ 35.0			Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L <sub>down</sub> =      ft V <sub>D</sub> =      veh/h				
<b>Conversion to pc/h Under Base Conditions</b>									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	1036	0.90 ✓	Level	6	0	0.971	0.90 ✓	1317	
Ramp	157	0.90 ✓	Level	22	0	0.901	0.90 ✓	215	
UpStream									
DownStream									
<b>Merge Areas</b>					<b>Diverge Areas</b>				
<b>Estimation of v<sub>12</sub></b>					<b>Estimation of v<sub>12</sub></b>				
$V_{12} = V_F (P_{FM})$ L <sub>EQ</sub> =      (Equation 13-6 or 13-7) P <sub>FM</sub> =      1.000 using Equation (Exhibit 13-6) V <sub>12</sub> =      1317 pc/h V <sub>3</sub> or V <sub>av34</sub> 0 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> =      pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ L <sub>EQ</sub> =      (Equation 13-12 or 13-13) P <sub>FD</sub> =      using Equation (Exhibit 13-7) V <sub>12</sub> =      pc/h V <sub>3</sub> or V <sub>av34</sub> pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> =      pc/h (Equation 13-16, 13-18, or 13-19)				
<b>Capacity Checks</b>					<b>Capacity Checks</b>				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>	1532	Exhibit 13-8		No	V <sub>F</sub>		Exhibit 13-8		
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>		Exhibit 13-8		
					V <sub>R</sub>		Exhibit 13-10		
<b>Flow Entering Merge Influence Area</b>					<b>Flow Entering Diverge Influence Area</b>				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>	1532	Exhibit 13-8		No	V <sub>12</sub>		Exhibit 13-8		
<b>Level of Service Determination (if not F)</b>					<b>Level of Service Determination (if not F)</b>				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> =      13.8 (pc/mi/ln) LOS =      B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> =      (pc/mi/ln) LOS =      (Exhibit 13-2)				

<b>RAMPS AND RAMP JUNCTIONS WORKSHEET</b>									
<b>General Information</b>					<b>Site Information</b>				
Analyst	AL				Freeway/Dir of Travel	I-75 WB			
Agency or Company	AIM ENGINEERING				Junction	SR 29 OFF RAMP			
Date Performed	3/8/2012				Jurisdiction				
Analysis Time Period	AM				Analysis Year	2019 EVERGLADES			
Project Description									
<b>Inputs</b>									
Upstream Adj Ramp		Number of Lanes, N			2 ✓			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Acceleration Lane Length, L <sub>A</sub>						<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Deceleration Lane Length L <sub>D</sub>			215			<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L <sub>up</sub> =      ft		Freeway Volume, V <sub>F</sub>			1518 ✓			L <sub>down</sub> =      ft	
V <sub>u</sub> =      veh/h		Ramp Volume, V <sub>R</sub>			201 ✓			V <sub>D</sub> =      veh/h	
		Freeway Free-Flow Speed, S <sub>FF</sub>			70.0 ✓				
		Ramp Free-Flow Speed, S <sub>FR</sub>			45.0 ✓				
<b>Conversion to pc/h Under Base Conditions</b>									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	1518	0.90 ✓	Level	6	0	0.971	0.90 ✓	1930	
Ramp	201	0.90 ✓	Level	22	0	0.901	0.90 ✓	275	
UpStream									
DownStream									
<b>Merge Areas</b>					<b>Diverge Areas</b>				
<b>Estimation of v<sub>12</sub></b>					<b>Estimation of v<sub>12</sub></b>				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L <sub>EQ</sub> = P <sub>FM</sub> = using Equation (Exhibit 13-6) V <sub>12</sub> = pc/h V <sub>3</sub> or V <sub>av34</sub> pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L <sub>EQ</sub> = P <sub>FD</sub> = 1.000 using Equation (Exhibit 13-7) V <sub>12</sub> = 1930 pc/h V <sub>3</sub> or V <sub>av34</sub> 0 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)				
<b>Capacity Checks</b>					<b>Capacity Checks</b>				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>		Exhibit 13-8			V <sub>F</sub>	1930	Exhibit 13-8	4800	No
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>	1655	Exhibit 13-8	4800	No
					V <sub>R</sub>	275	Exhibit 13-10	2100	No
<b>Flow Entering Merge Influence Area</b>					<b>Flow Entering Diverge Influence Area</b>				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>		Exhibit 13-8			V <sub>12</sub>	1930	Exhibit 13-8	4400:All	No
<b>Level of Service Determination (if not F)</b>					<b>Level of Service Determination (if not F)</b>				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> = 18.9 (pc/mi/ln) LOS = B (Exhibit 13-2)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	AL	Freeway/Dir of Travel	I-75 WB						
Agency or Company	AIM ENGINEERING	Junction	SR 29 WB ON						
Date Performed	3/16/2012	Jurisdiction							
Analysis Time Period	AM	Analysis Year	2019 EVERGLADES						
Project Description									
Inputs									
Upstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L <sub>up</sub> = ft V <sub>u</sub> = veh/h	Number of Lanes, N Acceleration Lane Length, L <sub>A</sub> Deceleration Lane Length L <sub>D</sub> Freeway Volume, V <sub>F</sub> Ramp Volume, V <sub>R</sub> Freeway Free-Flow Speed, S <sub>FF</sub> Ramp Free-Flow Speed, S <sub>FR</sub>	2 ✓ 415  1317 ✓ 434 ✓ 70.0 ✓ 35.0					Downstream Adj Ramp <input type="checkbox"/> Yes <input type="checkbox"/> On <input checked="" type="checkbox"/> No <input type="checkbox"/> Off L <sub>down</sub> = ft V <sub>D</sub> = veh/h		
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	1317	0.90 ✓	Level	6	0	0.971	0.90 ✓	1675	
Ramp	434	0.90 ✓	Level	22	0	0.901	0.90 ✓	595	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v <sub>12</sub>					Estimation of v <sub>12</sub>				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L <sub>EQ</sub> = P <sub>FM</sub> = 1.000 using Equation (Exhibit 13-6) V <sub>12</sub> = 1675 pc/h V <sub>3</sub> or V <sub>av34</sub> = 0 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L <sub>EQ</sub> = P <sub>FD</sub> = using Equation (Exhibit 13-7) V <sub>12</sub> = pc/h V <sub>3</sub> or V <sub>av34</sub> = pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>	2270	Exhibit 13-8		No	V <sub>F</sub>		Exhibit 13-8		
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>		Exhibit 13-8		
					V <sub>R</sub>		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>	2270	Exhibit 13-8 4600:All		No	V <sub>12</sub>		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> = 20.3 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> = (pc/mi/ln) LOS = (Exhibit 13-2)				

Phone: Fax:  
E-mail:

----- Diverge Analysis -----

Analyst: GSR  
Agency/Co.: AIM ENGINEERING  
Date performed: 3/27/2012  
Analysis time period: AM  
Freeway/Dir of Travel: I-75 EB  
Junction: EVERGLADES BLVD OFF RAMP  
Jurisdiction:  
Analysis Year: 2019 EVERGLADES  
Description:

----- Freeway Data -----

Type of analysis	Diverge	
Number of lanes in freeway	2	
Free-flow speed on freeway	70.0	mph
Volume on freeway	1799	vph

----- Off Ramp Data -----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	45.0	mph
Volume on ramp	518	vph
Length of first accel/decel lane	400	ft
Length of second accel/decel lane		ft

----- Adjacent Ramp Data (if one exists) -----

Does adjacent ramp exist?	No	
Volume on adjacent ramp		vph
Position of adjacent ramp		
Type of adjacent ramp		
Distance to adjacent ramp		ft

----- Conversion to pc/h Under Base Conditions -----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	1799	518		vph
Peak-hour factor, PHF	0.90	0.90		
Peak 15-min volume, v15	500	144		v
Trucks and buses	6	6		%
Recreational vehicles	0	0		%
Terrain type:	Level	Level		
Grade	0.00	%	0.00	%
Length	0.00	mi	0.00	mi
Trucks and buses PCE, ET	1.5*	1.5		
Recreational vehicle PCE, ER	1.2	1.2		

Heavy vehicle adjustment, fHV	0.971	0.971	
Driver population factor, fP	1.00	1.00	
Flow rate, vp	2059	593	pcph

Estimation of V12 Diverge Areas

L = (Equation 25-8 or 25-9)  
 EQ  
 P = 1.000 Using Equation 0  
 FD  
 $v_{12} = v_R + (v_F - v_R) P = 2059 \text{ pc/h}$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{12} = v_{Fi}$	2059	4800	No
$v_{FO} = v_F - v_R$	1466	4800	No
$v_R$	593	2100	No
$v_{3 \text{ or } 34}$	0 pc/h	(Equation 25-15 or 25-16)	
Is $v_{3 \text{ or } 34} > 2700 \text{ pc/h?}$		No	
Is $v_{3 \text{ or } 34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} =$		(Equation 25-18)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
$v_{12}$	2059	4600	No

Level of Service Determination (if not F)

Density,  $D = 4.252 + 0.0086 v_{12} - 0.009 L_D = 18.4 \text{ pc/mi/ln}$   
 Level of service for ramp-freeway junction areas of influence B

Speed Estimation

Intermediate speed variable,	D = 0.351	
Space mean speed in ramp influence area,	S = 60.2	mph
Space mean speed in outer lanes,	S = N/A	mph
Space mean speed for all vehicles,	S = 60.2	mph

Phone: Fax:  
E-mail:

----- Merge Analysis -----

Analyst: GSR  
Agency/Co.: AIM ENGINEERING  
Date performed: 3/28/2012  
Analysis time period: AM  
Freeway/Dir of Travel: I-75 EB  
Junction: EVERGLADES BLVD EB ON  
Jurisdiction:  
Analysis Year: 2019 EVERGLADES  
Description:

----- Freeway Data -----

Type of analysis	Merge	
Number of lanes in freeway	2	
Free-flow speed on freeway	70.0	mph
Volume on freeway	1281	vph

----- On Ramp Data -----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	35.0	mph
Volume on ramp	95	vph
Length of first accel/decel lane	1200	ft
Length of second accel/decel lane		ft

----- Adjacent Ramp Data (if one exists) -----

Does adjacent ramp exist?	No	
Volume on adjacent Ramp		vph
Position of adjacent Ramp		
Type of adjacent Ramp		
Distance to adjacent Ramp		ft

----- Conversion to pc/h Under Base Conditions -----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	1281	95		vph
Peak-hour factor, PHF	0.90	0.90		
Peak 15-min volume, v15	356	26		v
Trucks and buses	6	6		%
Recreational vehicles	0	0		%
Terrain type:	Level	Level		
Grade		%	%	%
Length		mi	mi	mi
Trucks and buses PCE, ET	1.5*	1.5		
Recreational vehicle PCE, ER	1.2	1.2		



Heavy vehicle adjustment, fHV	0.971	0.971	
Driver population factor, fP	0.90	0.90	
Flow rate, vp	1629	121	pcph

----- Estimation of V12 Merge Areas -----

L = (Equation 25-2 or 25-3)  
 EQ  
 P = 1.000 Using Equation 0  
 FM  
 $v_{12} = v_{F, FM} = 1629 \text{ pc/h}$

----- Capacity Checks -----

	Actual	Maximum	LOS F?
v <sub>FO</sub>	1750	4800	No
v <sub>3 or av34</sub>	0 pc/h	(Equation 25-4 or 25-5)	
Is v <sub>3 or av34</sub> > 2700 pc/h?		No	
Is v <sub>3 or av34</sub> > 1.5 v <sub>12</sub> / 2		No	
If yes, v <sub>12A</sub> =		(Equation 25-8)	

----- Flow Entering Merge Influence Area -----

	Actual	Max Desirable	Violation?
v <sub>12</sub>	1629	4400	No

----- Level of Service Determination (if not F) -----

Density,  $D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 11.5 \text{ pc/mi/ln}$   
 Level of service for ramp-freeway junction areas of influence B

----- Speed Estimation -----

Intermediate speed variable,	M = 0.259	
Space mean speed in ramp influence area,	S <sub>R</sub> = 62.7	mph
Space mean speed in outer lanes,	S <sub>0</sub> = N/A	mph
Space mean speed for all vehicles,	S = 62.7	mph

Phone: Fax:  
E-mail:

-----Diverge Analysis-----

Analyst: GSR  
Agency/Co.: AIM ENGINEERING  
Date performed: 3/28/2012  
Analysis time period: AM  
Freeway/Dir of Travel: I-75 WB  
Junction: EVERGLADES BLVD OFF RAMP  
Jurisdiction:  
Analysis Year: 2019 EVERGLADES  
Description:

-----Freeway Data-----

Type of analysis	Diverge	
Number of lanes in freeway	2	
Free-flow speed on freeway	70.0	mph
Volume on freeway	1751	vph

-----Off Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	45.0	mph
Volume on ramp	121	vph
Length of first accel/decel lane	400	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	No	
Volume on adjacent ramp		vph
Position of adjacent ramp		
Type of adjacent ramp		
Distance to adjacent ramp		ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	1751	121		vph
Peak-hour factor, PHF	0.90	0.90		
Peak 15-min volume, v15	486	34		v
Trucks and buses	6	6		%
Recreational vehicles	0	0		%
Terrain type:	Level	Level		
Grade	0.00	%	0.00	%
Length	0.00	mi	0.00	mi
Trucks and buses PCE, ET	1.5*	1.5		
Recreational vehicle PCE, ER	1.2	1.2		

Heavy vehicle adjustment, fHV	0.971	0.971	
Driver population factor, fP	0.90	0.90	
Flow rate, vp	2227	154	pcph

Estimation of V12 Diverge Areas

$L =$  (Equation 25-8 or 25-9)  
 EQ  
 $P =$  1.000 Using Equation 0  
 FD  
 $v = v + (v - v) P = 2227$  pc/h  
 12 R F R FD

Capacity Checks

	Actual	Maximum	LOS F?
$v = v$ Fi F	2227	4800	No
$v = v - v$ FO F R	2073	4800	No
v R	154	2100	No
$v v$ 3 or av34	0 pc/h	(Equation 25-15 or 25-16)	
Is $v v > 2700$ pc/h?		No	
$v v$ 3 or av34			
Is $v v > 1.5 v / 2$	12	No	
If yes, $v =$ 12A		(Equation 25-18)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v 12	2227	4600	No

Level of Service Determination (if not F)

Density,  $D = 4.252 + 0.0086 v - 0.009 L = 19.8$  pc/mi/ln  
 R 12 D  
 Level of service for ramp-freeway junction areas of influence B

Speed Estimation

Intermediate speed variable,	D = 0.312	
Space mean speed in ramp influence area,	S = 61.3	mph
Space mean speed in outer lanes,	S = N/A	mph
Space mean speed for all vehicles,	S = 61.3	mph

Phone: Fax:  
E-mail:

----- Merge Analysis -----

Analyst: GSR  
 Agency/Co.: AIM ENGINEERING  
 Date performed: 3/28/2012  
 Analysis time period: AM  
 Freeway/Dir of Travel: I-75 WB  
 Junction: EVERGLADES BLVD WB ON  
 Jurisdiction:  
 Analysis Year: 2019 EVERGLADES  
 Description:

----- Freeway Data -----

Type of analysis	Merge	
Number of lanes in freeway	2	
Free-flow speed on freeway	70.0	mph
Volume on freeway	1630	vph

----- On Ramp Data -----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	35.0	mph
Volume on ramp	659	vph
Length of first accel/decel lane	1200	ft
Length of second accel/decel lane		ft

----- Adjacent Ramp Data (if one exists) -----

Does adjacent ramp exist?	No	
Volume on adjacent Ramp		vph
Position of adjacent Ramp		
Type of adjacent Ramp		
Distance to adjacent Ramp		ft

----- Conversion to pc/h Under Base Conditions -----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	1630	659		vph
Peak-hour factor, PHF	0.90	0.90		
Peak 15-min volume, v15	453	183		v
Trucks and buses	6	6		%
Recreational vehicles	0	0		%
Terrain type:	Level	Level		
Grade		%	%	%
Length		mi	mi	mi
Trucks and buses PCE, ET	1.5*	1.5		
Recreational vehicle PCE, ER	1.2	1.2		

Heavy vehicle adjustment, fHV	0.971	0.971	
Driver population factor, fP	1.00	1.00	
Flow rate, vp	1865	754	pcph

----- Estimation of V12 Merge Areas -----

L = (Equation 25-2 or 25-3)  
EQ  
P = 1.000 Using Equation 0  
FM  
 $v_{12} = v_F (P_{FM}) = 1865 \text{ pc/h}$

----- Capacity Checks -----

	Actual	Maximum	LOS F?
v <sub>FO</sub>	2619	4800	No
v <sub>3 or av34</sub>	0 pc/h	(Equation 25-4 or 25-5)	
Is v <sub>3 or av34</sub> > 2700 pc/h?		No	
Is v <sub>3 or av34</sub> > 1.5 v <sub>12</sub> / 2		No	
If yes, v <sub>12A</sub> =		(Equation 25-8)	

----- Flow Entering Merge Influence Area -----

	Actual	Max Desirable	Violation?
v <sub>12</sub>	1865	4400	No

----- Level of Service Determination (if not F) -----

Density,  $D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 18.0 \text{ pc/mi/ln}$   
Level of service for ramp-freeway junction areas of influence B

----- Speed Estimation -----

Intermediate speed variable,	M = 0.291	
Space mean speed in ramp influence area,	S <sub>R</sub> = 61.9	mph
Space mean speed in outer lanes,	S <sub>0</sub> = N/A	mph
Space mean speed for all vehicles,	S = 61.9	mph

-----

Phone: Fax:  
E-mail:

----- Diverge Analysis -----

Analyst: GSR  
Agency/Co.: AIM ENGINEERING  
Date performed: 4/4/2012  
Analysis time period: AM  
Freeway/Dir of Travel: I-75 EB  
Junction: SR 951 OFF RAMP  
Jurisdiction:  
Analysis Year: 2019 EVERGLADES  
Description:

----- Freeway Data -----

Type of analysis	Diverge	
Number of lanes in freeway	2	
Free-flow speed on freeway	70.0	mph
Volume on freeway	2786	vph

----- Off Ramp Data -----

Side of freeway	Right	
Number of lanes in ramp	2	
Free-Flow speed on ramp	45.0	mph
Volume on ramp	1461	vph
Length of first accel/decel lane	500	ft
Length of second accel/decel lane	0	ft

----- Adjacent Ramp Data (if one exists) -----

Does adjacent ramp exist?	No	
Volume on adjacent ramp		vph
Position of adjacent ramp		
Type of adjacent ramp		
Distance to adjacent ramp		ft

----- Conversion to pc/h Under Base Conditions -----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	2786	1461		vph
Peak-hour factor, PHF	0.90	0.90		
Peak 15-min volume, v15	774	406		v
Trucks and buses	6	6		%
Recreational vehicles	0	0		%
Terrain type:	Level	Level		
Grade	0.00	%	0.00	%
Length	0.00	mi	0.00	mi
Trucks and buses PCE, ET	1.5*	1.5		
Recreational vehicle PCE, ER	1.2	1.2		



Heavy vehicle adjustment, fHV	0.971	0.971	
Driver population factor, fP	1.00	1.00	
Flow rate, vp	3188	1672	pcph

----- Estimation of V12 Diverge Areas -----

L = (Equation 25-8 or 25-9)  
 EQ  
 P = 1.000 Using Equation 0  
 FD  
 $v_{12} = v_R + (v_F - v_R) P = 3188 \text{ pc/h}$

----- Capacity Checks -----

	Actual	Maximum	LOS F?
$v_{12} = v_{Fi}$	3188	4800	No
$v_{FO} = v_F - v_R$	1516	4800	No
$v_R$	1672	4100	No
$v_{3 \text{ or } 34}$	0 pc/h	(Equation 25-15 or 25-16)	
Is $v_{3 \text{ or } 34} > 2700 \text{ pc/h?}$		No	
Is $v_{3 \text{ or } 34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} =$		(Equation 25-18)	

----- Flow Entering Diverge Influence Area -----

	Actual	Max Desirable	Violation?
$v_{12}$	3188	4600	No

----- Level of Service Determination (if not F) -----

Density,  $D = 4.252 + 0.0086 v_{12} - 0.009 L_D = 22.7 \text{ pc/mi/ln}$   
 Level of service for ramp-freeway junction areas of influence C

----- Speed Estimation -----

Intermediate speed variable,	D = 0.448	
Space mean speed in ramp influence area,	S = 57.4	mph
Space mean speed in outer lanes,	S = N/A	mph
Space mean speed for all vehicles,	S = 57.4	mph

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	AL				Freeway/Dir of Travel	I-75 EB			
Agency or Company	AIM ENGINEERING				Junction	SR 951 EB ON			
Date Performed	3/16/2012				Jurisdiction				
Analysis Time Period	AM				Analysis Year	2019 EVERGLADES			
Project Description									
Inputs									
Upstream Adj Ramp		Number of Lanes, N			2			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Acceleration Lane Length, L <sub>A</sub>			465			<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Deceleration Lane Length L <sub>D</sub>						<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L <sub>up</sub> =        ft		Freeway Volume, V <sub>F</sub>			1325			L <sub>down</sub> =        ft	
V <sub>u</sub> =        veh/h		Ramp Volume, V <sub>R</sub>			474			V <sub>D</sub> =        veh/h	
		Freeway Free-Flow Speed, S <sub>FF</sub>			70.0				
		Ramp Free-Flow Speed, S <sub>FR</sub>			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	1325	0.90	Level	6	0	0.971	1.00	1516	
Ramp	474	0.90	Level	6	0	0.971	1.00	542	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v <sub>12</sub>					Estimation of v <sub>12</sub>				
L <sub>EQ</sub> =		V <sub>12</sub> = V <sub>F</sub> (P <sub>FM</sub> )			L <sub>EQ</sub> =		V <sub>12</sub> = V <sub>R</sub> + (V <sub>F</sub> - V <sub>R</sub> )P <sub>FD</sub>		
		(Equation 13-6 or 13-7)					(Equation 13-12 or 13-13)		
P <sub>FM</sub> =		1.000 using Equation (Exhibit 13-6)			P <sub>FD</sub> =		using Equation (Exhibit 13-7)		
V <sub>12</sub> =		1516 pc/h			V <sub>12</sub> =		pc/h		
V <sub>3</sub> or V <sub>av34</sub>		0 pc/h (Equation 13-14 or 13-17)			V <sub>3</sub> or V <sub>av34</sub>		pc/h (Equation 13-14 or 13-17)		
Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h?		<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No			Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h?		<input type="checkbox"/> Yes <input type="checkbox"/> No		
Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2		<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No			Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2		<input type="checkbox"/> Yes <input type="checkbox"/> No		
If Yes, V <sub>12a</sub> =		pc/h (Equation 13-16, 13-18, or 13-19)			If Yes, V <sub>12a</sub> =		pc/h (Equation 13-16, 13-18, or 13-19)		
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>	2058	Exhibit 13-8		No	V <sub>F</sub>		Exhibit 13-8		
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>		Exhibit 13-8		
					V <sub>R</sub>		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>	2058	Exhibit 13-8		No	V <sub>12</sub>		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
D <sub>R</sub> = 5.475 + 0.00734 v <sub>R</sub> + 0.0078 V <sub>12</sub> - 0.00627 L <sub>A</sub>					D <sub>R</sub> = 4.252 + 0.0086 V <sub>12</sub> - 0.009 L <sub>D</sub>				
D <sub>R</sub> = 18.4 (pc/mi/ln)					D <sub>R</sub> = (pc/mi/ln)				
LOS = B (Exhibit 13-2)					LOS = (Exhibit 13-2)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	AL	Freeway/Dir of Travel	I-75 WB						
Agency or Company	AIM ENGINEERING	Junction	SR 951 OFF RAMP						
Date Performed	3/8/2012	Jurisdiction							
Analysis Time Period	AM	Analysis Year	2019 EVERGLADES						
Project Description									
Inputs									
Upstream Adj Ramp		Number of Lanes, N		2 ✓		Downstream Adj Ramp			
<input type="checkbox"/> Yes <input type="checkbox"/> On		Acceleration Lane Length, L <sub>A</sub>				<input type="checkbox"/> Yes <input type="checkbox"/> On			
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Deceleration Lane Length L <sub>D</sub>		220		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off			
L <sub>up</sub> = ft		Freeway Volume, V <sub>F</sub>		2289 ✓		L <sub>down</sub> = ft			
V <sub>u</sub> = veh/h		Ramp Volume, V <sub>R</sub>		603 ✓		V <sub>D</sub> = veh/h			
		Freeway Free-Flow Speed, S <sub>FF</sub>		70.0 ✓					
		Ramp Free-Flow Speed, S <sub>FR</sub>		45.0 ✓					
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	2289	0.90 ✓	Level	6	0	0.971	1.00 ✓	2620	
Ramp	603	0.90 ✓	Level	6	0	0.971	1.00 ✓	690	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v <sub>12</sub>					Estimation of v <sub>12</sub>				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L <sub>EQ</sub> = P <sub>FM</sub> = using Equation (Exhibit 13-6) V <sub>12</sub> = pc/h V <sub>3</sub> or V <sub>av34</sub> pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L <sub>EQ</sub> = P <sub>FD</sub> = 1.000 using Equation (Exhibit 13-7) V <sub>12</sub> = 2620 pc/h V <sub>3</sub> or V <sub>av34</sub> 0 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>		Exhibit 13-8			V <sub>F</sub>	2620	Exhibit 13-8	4800	No
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>	1930	Exhibit 13-8	4800	No
					V <sub>R</sub>	690	Exhibit 13-10	2100	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>		Exhibit 13-8			V <sub>12</sub>	2620	Exhibit 13-8	4400:All	No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> = 24.8 (pc/mi/ln) LOS = C (Exhibit 13-2)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	AL		Freeway/Dir of Travel	I-75 WB					
Agency or Company	AIM ENGINEERING		Junction	SR 951 WB ON					
Date Performed	3/16/2012		Jurisdiction						
Analysis Time Period	AM		Analysis Year	2019 EVERGLADES					
Project Description									
Inputs									
Upstream Adj Ramp		Number of Lanes, N		2 ✓		Downstream Adj Ramp			
<input type="checkbox"/> Yes <input type="checkbox"/> On		Acceleration Lane Length, L <sub>A</sub>		385		<input type="checkbox"/> Yes <input type="checkbox"/> On			
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Deceleration Lane Length L <sub>D</sub>				<input checked="" type="checkbox"/> No <input type="checkbox"/> Off			
L <sub>up</sub> = ft		Freeway Volume, V <sub>F</sub>		1686 ✓		L <sub>down</sub> = ft			
V <sub>u</sub> = veh/h		Ramp Volume, V <sub>R</sub>		1859 ✓		V <sub>D</sub> = veh/h			
		Freeway Free-Flow Speed, S <sub>FF</sub>		70.0 ✓					
		Ramp Free-Flow Speed, S <sub>FR</sub>		35.0					
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	1686	0.90 ✓	Level	6	0	0.971	1.00 ✓	1930	
Ramp	1859	0.90 ✓	Level	6	0	0.971	1.00 ✓	2128	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v <sub>12</sub>					Estimation of v <sub>12</sub>				
$V_{12} = V_F (P_{FM})$ L <sub>EQ</sub> = (Equation 13-6 or 13-7) P <sub>FM</sub> = 1.000 using Equation (Exhibit 13-6) V <sub>12</sub> = 1930 pc/h V <sub>3</sub> or V <sub>av34</sub> = 0 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ L <sub>EQ</sub> = (Equation 13-12 or 13-13) P <sub>FD</sub> = using Equation (Exhibit 13-7) V <sub>12</sub> = pc/h V <sub>3</sub> or V <sub>av34</sub> = pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>	4058	Exhibit 13-8		No	V <sub>F</sub>		Exhibit 13-8		
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>		Exhibit 13-8		
					V <sub>R</sub>		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>	4058	Exhibit 13-8		4600:All	No	V <sub>12</sub>	Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> = 33.7 (pc/mi/ln) LOS = D (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> = (pc/mi/ln) LOS = (Exhibit 13-2)				


RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	AL	Freeway/Dir of Travel	I-75 NB						
Agency or Company	AIM ENGINEERING	Junction	GGP NB OFF RAMP						
Date Performed	3/8/2012	Jurisdiction							
Analysis Time Period	AM	Analysis Year	2019 EVERGLADES						
Project Description									
Inputs									
Upstream Adj Ramp		Number of Lanes, N		3 ✓		Downstream Adj Ramp			
<input type="checkbox"/> Yes <input type="checkbox"/> On		Acceleration Lane Length, L <sub>A</sub>				<input type="checkbox"/> Yes <input type="checkbox"/> On			
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Deceleration Lane Length L <sub>D</sub>		310		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off			
L <sub>up</sub> = ft		Freeway Volume, V <sub>F</sub>		3545 ✓		L <sub>down</sub> = ft			
V <sub>u</sub> = veh/h		Ramp Volume, V <sub>R</sub>		556 ✓		V <sub>D</sub> = veh/h			
		Freeway Free-Flow Speed, S <sub>FF</sub>		70.0 ✓					
		Ramp Free-Flow Speed, S <sub>FR</sub>		45.0 ✓					
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	3545	0.90 ✓	Level	6	0	0.971	1.00 ✓	4057	
Ramp	556	0.90 ✓	Level	6	0	0.971	1.00 ✓	636	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v <sub>12</sub>					Estimation of v <sub>12</sub>				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L <sub>EQ</sub> = P <sub>FM</sub> = using Equation (Exhibit 13-6) V <sub>12</sub> = pc/h V <sub>3</sub> or V <sub>av34</sub> pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L <sub>EQ</sub> = P <sub>FD</sub> = 0.629 using Equation (Exhibit 13-7) V <sub>12</sub> = 2789 pc/h V <sub>3</sub> or V <sub>av34</sub> 1268 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>		Exhibit 13-8			V <sub>F</sub>	4057	Exhibit 13-8	7200	No
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>	3421	Exhibit 13-8	7200	No
					V <sub>R</sub>	636	Exhibit 13-10	2100	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>		Exhibit 13-8			V <sub>12</sub>	2789	Exhibit 13-8	4400:All	No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> = 25.4 (pc/mi/ln) LOS = C (Exhibit 13-2)				

BASIC FREEWAY SEGMENTS WORKSHEET																								
		<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Application</th> <th>Input</th> <th>Output</th> </tr> </thead> <tbody> <tr> <td>Operational (LOS)</td> <td>FFS, N, <math>v_p</math></td> <td>LOS, S, D</td> </tr> <tr> <td>Design (N)</td> <td>FFS, LOS, <math>v_p</math></td> <td>N, S, D</td> </tr> <tr> <td>Design (<math>v_p</math>)</td> <td>FFS, LOS, N</td> <td><math>v_p</math>, S, D</td> </tr> <tr> <td>Planning (LOS)</td> <td>FFS, N, AADT</td> <td>LOS, S, D</td> </tr> <tr> <td>Planning (N)</td> <td>FFS, LOS, AADT</td> <td>N, S, D</td> </tr> <tr> <td>Planning (<math>v_p</math>)</td> <td>FFS, LOS, N</td> <td><math>v_p</math>, S, D</td> </tr> </tbody> </table>		Application	Input	Output	Operational (LOS)	FFS, N, $v_p$	LOS, S, D	Design (N)	FFS, LOS, $v_p$	N, S, D	Design ( $v_p$ )	FFS, LOS, N	$v_p$ , S, D	Planning (LOS)	FFS, N, AADT	LOS, S, D	Planning (N)	FFS, LOS, AADT	N, S, D	Planning ( $v_p$ )	FFS, LOS, N	$v_p$ , S, D
Application	Input	Output																						
Operational (LOS)	FFS, N, $v_p$	LOS, S, D																						
Design (N)	FFS, LOS, $v_p$	N, S, D																						
Design ( $v_p$ )	FFS, LOS, N	$v_p$ , S, D																						
Planning (LOS)	FFS, N, AADT	LOS, S, D																						
Planning (N)	FFS, LOS, AADT	N, S, D																						
Planning ( $v_p$ )	FFS, LOS, N	$v_p$ , S, D																						
<b>General Information</b>		<b>Site Information</b>																						
Analyst	GSR	Highway/Direction of Travel	I-75																					
Agency or Company	AIM ENGINEERING	From/To	BTWN NB GG PKW ON/OFF-RAMPS																					
Date Performed	3/26/2012	Jurisdiction																						
Analysis Time Period	AM	Analysis Year	2019 EVERGLADES																					
Project Description EVERGLADES IJR																								
<input type="checkbox"/> Oper.(LOS)		<input type="checkbox"/> Des.(N)																						
<input type="checkbox"/> Planning Data																								
<b>Flow Inputs</b>																								
Volume, V	2989	veh/h	Peak-Hour Factor, PHF																					
AADT		veh/day	%Trucks and Buses, $P_T$																					
Peak-Hr Prop. of AADT, K			%RVs, $P_R$																					
Peak-Hr Direction Prop, D			General Terrain:																					
DDHV = AADT x K x D		veh/h	Grade % Length																					
Driver type adjustment	1.00		Up/Down %																					
<b>Calculate Flow Adjustments</b>																								
$f_p$	1.00	$E_R$	1.2																					
$E_T$	1.5	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	0.971																					
<b>Speed Inputs</b>		<b>Calc Speed Adj and FFS</b>																						
Lane Width	12.0	ft	$f_{LW}$																					
Rt-Shoulder Lat. Clearance	6.0	ft	$f_{LC}$																					
Interchange Density	0.50	l/mi	$f_{ID}$																					
Number of Lanes, N	2		$f_N$																					
FFS (measured)		mi/h	FFS																					
Base free-flow Speed, BFFS	75.0	mi/h																						
<b>LOS and Performance Measures</b>		<b>Design (N)</b>																						
<u>Operational (LOS)</u>		<u>Design (N)</u>																						
$v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$	1710	pc/h/ln	Design LOS																					
S	69.1	mi/h	$v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$																					
$D = v_p / S$	24.7	pc/mi/ln	S																					
LOS	C		$D = v_p / S$																					
		Required Number of Lanes, N																						
<b>Glossary</b>		<b>Factor Location</b>																						
N - Number of lanes	S - Speed	$E_R$ - Exhibits 23-8, 23-10	$f_{LW}$ - Exhibit 23-4																					
V - Hourly volume	D - Density	$E_T$ - Exhibits 23-8, 23-10, 23-11	$f_{LC}$ - Exhibit 23-5																					
$v_p$ - Flow rate	FFS - Free-flow speed	$f_p$ - Page 23-12	$f_N$ - Exhibit 23-6																					
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, $v_p$ - Exhibits 23-2, 23-3	$f_{ID}$ - Exhibit 23-7																					
DDHV - Directional design hour volume																								



BASIC FREEWAY SEGMENTS WORKSHEET																								
		<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Application</th> <th>Input</th> <th>Output</th> </tr> </thead> <tbody> <tr> <td>Operational (LOS)</td> <td>FFS, N, <math>v_p</math></td> <td>LOS, S, D</td> </tr> <tr> <td>Design (N)</td> <td>FFS, LOS, <math>v_p</math></td> <td>N, S, D</td> </tr> <tr> <td>Design (<math>v_p</math>)</td> <td>FFS, LOS, N</td> <td><math>v_p</math>, S, D</td> </tr> <tr> <td>Planning (LOS)</td> <td>FFS, N, AADT</td> <td>LOS, S, D</td> </tr> <tr> <td>Planning (N)</td> <td>FFS, LOS, AADT</td> <td>N, S, D</td> </tr> <tr> <td>Planning (<math>v_p</math>)</td> <td>FFS, LOS, N</td> <td><math>v_p</math>, S, D</td> </tr> </tbody> </table>		Application	Input	Output	Operational (LOS)	FFS, N, $v_p$	LOS, S, D	Design (N)	FFS, LOS, $v_p$	N, S, D	Design ( $v_p$ )	FFS, LOS, N	$v_p$ , S, D	Planning (LOS)	FFS, N, AADT	LOS, S, D	Planning (N)	FFS, LOS, AADT	N, S, D	Planning ( $v_p$ )	FFS, LOS, N	$v_p$ , S, D
Application	Input	Output																						
Operational (LOS)	FFS, N, $v_p$	LOS, S, D																						
Design (N)	FFS, LOS, $v_p$	N, S, D																						
Design ( $v_p$ )	FFS, LOS, N	$v_p$ , S, D																						
Planning (LOS)	FFS, N, AADT	LOS, S, D																						
Planning (N)	FFS, LOS, AADT	N, S, D																						
Planning ( $v_p$ )	FFS, LOS, N	$v_p$ , S, D																						
<b>General Information</b>		<b>Site Information</b>																						
Analyst	AL	Highway/Direction of Travel	I-75																					
Agency or Company	AIM ENGINEERING	From/To	N OF GG PKWY_NB																					
Date Performed	3/6/2012	Jurisdiction																						
Analysis Time Period	AM	Analysis Year	2019 EVERGLADES																					
Project Description EVERGLADES IJR																								
<input type="checkbox"/> Oper.(LOS)		<input type="checkbox"/> Des.(N)																						
<input type="checkbox"/> Planning Data																								
<b>Flow Inputs</b>																								
Volume, V	4514	veh/h	Peak-Hour Factor, PHF																					
AADT		veh/day	%Trucks and Buses, $P_T$																					
Peak-Hr Prop. of AADT, K			%RVs, $P_R$																					
Peak-Hr Direction Prop, D			General Terrain:																					
DDHV = AADT x K x D		veh/h	Grade % Length																					
Driver type adjustment	1.00		Up/Down %																					
<b>Calculate Flow Adjustments</b>																								
$f_p$	1.00		$E_R$																					
$E_T$	1.5		$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$																					
<b>Speed Inputs</b>		<b>Calc Speed Adj and FFS</b>																						
Lane Width	12.0	ft	$f_{LW}$																					
Rt-Shoulder Lat. Clearance	6.0	ft	$f_{LC}$																					
Interchange Density	0.50	l/mi	$f_{ID}$																					
Number of Lanes, N	3		$f_N$																					
FFS (measured)		mi/h	FFS																					
Base free-flow Speed, BFFS	75.0	mi/h																						
<b>LOS and Performance Measures</b>		<b>Design (N)</b>																						
<b>Operational (LOS)</b>		<b>Design (N)</b>																						
$v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$	1722	pc/h/ln	Design LOS																					
S	70.1	mi/h	$v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$																					
$D = v_p / S$	24.6	pc/mi/ln	S																					
LOS	C		$D = v_p / S$																					
		Required Number of Lanes, N																						
<b>Glossary</b>		<b>Factor Location</b>																						
N - Number of lanes	S - Speed	$E_R$ - Exhibits 23-8, 23-10	$f_{LW}$ - Exhibit 23-4																					
V - Hourly volume	D - Density	$E_T$ - Exhibits 23-8, 23-10, 23-11	$f_{LC}$ - Exhibit 23-5																					
$v_p$ - Flow rate	FFS - Free-flow speed	$f_p$ - Page 23-12	$f_N$ - Exhibit 23-6																					
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, $v_p$ - Exhibits 23-2, 23-3	$f_{ID}$ - Exhibit 23-7																					
DDHV - Directional design hour volume																								





General Information		Site Information	
Analyst	AL	Highway/Direction of Travel	I-75
Agency or Company	AIM ENGINEERING	From/To	N OF GG PKWY_SB
Date Performed	3/6/2012	Jurisdiction	
Analysis Time Period	AM	Analysis Year	2019 EVERGLADES

Project Description EVERGLADES IJR

Oper.(LOS)                       Des.(N)                       Planning Data

#### Flow Inputs

Volume, V	4360	veh/h	Peak-Hour Factor, PHF	0.90
AADT		veh/day	%Trucks and Buses, $P_T$	6
Peak-Hr Prop. of AADT, K			%RVs, $P_R$	0
Peak-Hr Direction Prop, D			General Terrain:	Level
DDHV = AADT x K x D		veh/h	Grade % Length	mi
Driver type adjustment	1.00		Up/Down %	


#### Calculate Flow Adjustments

$f_p$	1.00	$E_R$	1.2
$E_T$	1.5	$f_{HV} = 1/[1+P_T(E_T - 1) + P_R(E_R - 1)]$	0.971

Speed Inputs		Calc Speed Adj and FFS			
Lane Width	12.0	ft	$f_{LW}$	0.0	mi/h
Rt-Shoulder Lat. Clearance	6.0	ft	$f_{LC}$	0.0	mi/h
Interchange Density	0.50	l/mi	$f_{ID}$	0.0	mi/h
Number of Lanes, N	3		$f_N$	3.0	mi/h
FFS (measured)		mi/h	FFS	72.0	mi/h
Base free-flow Speed, BFFS	75.0	mi/h			

LOS and Performance Measures		Design (N)	
<u>Operational (LOS)</u>		<u>Design (N)</u>	
$v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$	1663	Design LOS	
S	70.6	$v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$	pc/h
$D = v_p / S$	23.5	S	mi/h
LOS	C	$D = v_p / S$	pc/mi/ln
		Required Number of Lanes, N	

Glossary		Factor Location	
N - Number of lanes	S - Speed	$E_R$ - Exhibits 23-8, 23-10	$f_{LW}$ - Exhibit 23-4
V - Hourly volume	D - Density	$E_T$ - Exhibits 23-8, 23-10, 23-11	$f_{LC}$ - Exhibit 23-5
$v_p$ - Flow rate	FFS - Free-flow speed	$f_p$ - Page 23-12	$f_N$ - Exhibit 23-6
LOS - Level of service	BFFS - Base free-flow speed	LOS, S, FFS, $v_p$ - Exhibits 23-2, 23-3	$f_{ID}$ - Exhibit 23-7
DDHV - Directional design hour volume			



General Information		Site Information	
Analyst	GSR	Highway/Direction of Travel	I-75
Agency or Company	AIM ENGINEERING	From/To	BTWN SB GG PKW ON-OFF-RAMPS
Date Performed	3/26/2012	Jurisdiction	
Analysis Time Period	AM	Analysis Year	2019 EVERGLADES
Project Description EVERGLADES IJR			

Oper.(LOS)                       Des.(N)                       Planning Data

#### Flow Inputs

Volume, V	2348	veh/h	Peak-Hour Factor, PHF	0.90
AADT		veh/day	%Trucks and Buses, $P_T$	6
Peak-Hr Prop. of AADT, K			%RVs, $P_R$	0
Peak-Hr Direction Prop, D			General Terrain:	Level
DDHV = AADT x K x D		veh/h	Grade % Length	mi
Driver type adjustment	1.00		Up/Down %	

#### Calculate Flow Adjustments

$f_p$	1.00	$E_R$	1.2
$E_T$	1.5	$f_{HV} = 1 / [(1 + P_T(E_T - 1) + P_R(E_R - 1))]$	0.971

Speed Inputs		Calc Speed Adj and FFS			
Lane Width	12.0	ft	$f_{LW}$	0.0	mi/h
Rt-Shoulder Lat. Clearance	6.0	ft	$f_{LC}$	0.0	mi/h
Interchange Density	0.50	l/mi	$f_{ID}$	0.0	mi/h
Number of Lanes, N	2		$f_N$	4.5	mi/h
FFS (measured)		mi/h	FFS	70.5	mi/h
Base free-flow Speed, BFFS	75.0	mi/h			

LOS and Performance Measures	Design (N)
Operational (LOS)	Design (N)
$v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$	Design LOS
1344	$v_p = (V \text{ or } DDHV) / (PHF \times N \times f_{HV} \times f_p)$
pc/h/ln	pc/h
S	70.5
mi/h	mi/h
$D = v_p / S$	D = $v_p / S$
19.1	pc/mi/ln
pc/mi/ln	Required Number of Lanes, N
LOS	C

Glossary	Factor Location
N - Number of lanes	S - Speed
V - Hourly volume	D - Density
$v_p$ - Flow rate	FFS - Free-flow speed
LOS - Level of service	BFFS - Base free-flow speed
DDHV - Directional design hour volume	
	$E_R$ - Exhibits 23-8, 23-10
	$E_T$ - Exhibits 23-8, 23-10, 23-11
	$f_p$ - Page 23-12
	LOS, S, FFS, $v_p$ - Exhibits 23-2, 23-3
	$f_{LW}$ - Exhibit 23-4
	$f_{LC}$ - Exhibit 23-5
	$f_N$ - Exhibit 23-6
	$f_{ID}$ - Exhibit 23-7

<b>RAMPS AND RAMP JUNCTIONS WORKSHEET</b>									
<b>General Information</b>					<b>Site Information</b>				
Analyst	AL		Freeway/Dir of Travel	I-75 SB					
Agency or Company	AIM ENGINEERING		Junction	GOLDEN GATE PKWY SB ON					
Date Performed	3/16/2012		Jurisdiction						
Analysis Time Period	AM		Analysis Year	2019 EVERGLADES					
Project Description									
<b>Inputs</b>									
Upstream Adj Ramp	Number of Lanes, N			3 ✓			Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On	Acceleration Lane Length, L <sub>A</sub>			550			<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	Deceleration Lane Length L <sub>D</sub>						<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L <sub>up</sub> =    ft	Freeway Volume, V <sub>F</sub>			2348 ✓			L <sub>down</sub> =    ft		
V <sub>u</sub> =    veh/h	Ramp Volume, V <sub>R</sub>			438 ✓			V <sub>D</sub> =    veh/h		
	Freeway Free-Flow Speed, S <sub>FF</sub>			70.0 ✓					
	Ramp Free-Flow Speed, S <sub>FR</sub>			35.0					
<b>Conversion to pc/h Under Base Conditions</b>									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	2348	0.90 ✓	Level	6	0	0.971	1.00 ✓	2687	
Ramp	438	0.90 ✓	Level	6	0	0.971	1.00 ✓	501	
UpStream									
DownStream									
<b>Merge Areas</b>					<b>Diverge Areas</b>				
<b>Estimation of v<sub>12</sub></b>					<b>Estimation of v<sub>12</sub></b>				
L <sub>EQ</sub> =	V <sub>12</sub> = V <sub>F</sub> (P <sub>FM</sub> )				V <sub>12</sub> = V <sub>R</sub> + (V <sub>F</sub> - V <sub>R</sub> )P <sub>FD</sub>				
	(Equation 13-6 or 13-7)				(Equation 13-12 or 13-13)				
P <sub>FM</sub> =	0.593 using Equation (Exhibit 13-6)				P <sub>FD</sub> =				
					using Equation (Exhibit 13-7)				
V <sub>12</sub> =	1593 pc/h				V <sub>12</sub> =				
					pc/h				
V <sub>3</sub> or V <sub>av34</sub>	1094 pc/h (Equation 13-14 or 13-17)				V <sub>3</sub> or V <sub>av34</sub>				
					pc/h (Equation 13-14 or 13-17)				
Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h?	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No				
Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No				
If Yes, V <sub>12a</sub> =	pc/h (Equation 13-16, 13-18, or 13-19)				If Yes, V <sub>12a</sub> =				
					pc/h (Equation 13-16, 13-18, or 13-19)				
<b>Capacity Checks</b>					<b>Capacity Checks</b>				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>	3188	Exhibit 13-8		No	V <sub>F</sub>		Exhibit 13-8		
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>		Exhibit 13-8		
					V <sub>R</sub>		Exhibit 13-10		
<b>Flow Entering Merge Influence Area</b>					<b>Flow Entering Diverge Influence Area</b>				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V <sub>R12</sub>	2094	Exhibit 13-8		No	V <sub>12</sub>		Exhibit 13-8		
<b>Level of Service Determination (if not F)</b>					<b>Level of Service Determination (if not F)</b>				
D <sub>R</sub> = 5.475 + 0.00734 v <sub>R</sub> + 0.0078 V <sub>12</sub> - 0.00627 L <sub>A</sub>					D <sub>R</sub> = 4.252 + 0.0086 V <sub>12</sub> - 0.009 L <sub>D</sub>				
D <sub>R</sub> = 18.1 (pc/mi/ln)					D <sub>R</sub> = (pc/mi/ln)				
LOS = B (Exhibit B-2)									

<b>RAMPS AND RAMP JUNCTIONS WORKSHEET</b>									
<b>General Information</b>					<b>Site Information</b>				
Analyst	AL	Freeway/Dir of Travel	I-75 EB						
Agency or Company	AIM ENGINEERING	Junction	SR 29 OFF RAMP						
Date Performed	3/8/2012	Jurisdiction							
Analysis Time Period	PM	Analysis Year	2019 EVERGLADES						
Project Description									
<b>Inputs</b>									
Upstream Adj Ramp	Number of Lanes, N		2 ✓		Downstream Adj Ramp				
<input type="checkbox"/> Yes <input type="checkbox"/> On	Acceleration Lane Length, L <sub>A</sub>				<input type="checkbox"/> Yes <input type="checkbox"/> On				
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	Deceleration Lane Length L <sub>D</sub>		202		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off				
L <sub>up</sub> = ft	Freeway Volume, V <sub>F</sub>		1751 ✓		L <sub>down</sub> = ft				
V <sub>u</sub> = veh/h	Ramp Volume, V <sub>R</sub>		434 ✓		V <sub>D</sub> = veh/h				
	Freeway Free-Flow Speed, S <sub>FF</sub>		70.0 ✓						
	Ramp Free-Flow Speed, S <sub>FR</sub>		45.0						
<b>Conversion to pc/h Under Base Conditions</b>									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>	
Freeway	1751	0.90 ✓	Level	6	0	0.971	0.90 ✓	2227	
Ramp	434	0.90 ✓	Level	22	0	0.901	0.90 ✓	595	
UpStream									
DownStream									
<b>Merge Areas</b>					<b>Diverge Areas</b>				
<b>Estimation of v<sub>12</sub></b>					<b>Estimation of v<sub>12</sub></b>				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L <sub>EQ</sub> = P <sub>FM</sub> = using Equation (Exhibit 13-6) V <sub>12</sub> = pc/h V <sub>3</sub> or V <sub>av34</sub> pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L <sub>EQ</sub> = P <sub>FD</sub> = 1.000 using Equation (Exhibit 13-7) V <sub>12</sub> = 2227 pc/h V <sub>3</sub> or V <sub>av34</sub> 0 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)				
<b>Capacity Checks</b>					<b>Capacity Checks</b>				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V <sub>FO</sub>		Exhibit 13-8			V <sub>F</sub>	2227	Exhibit 13-8	4800	No
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>	1632	Exhibit 13-8	4800	No
					V <sub>R</sub>	595	Exhibit 13-10	2100	No
<b>Flow Entering Merge Influence Area</b>					<b>Flow Entering Diverge Influence Area</b>				
	Actual	Max Desirable	Violation?			Actual	Max Desirable	Violation?	
V <sub>R12</sub>		Exhibit 13-8			V <sub>12</sub>	2227	Exhibit 13-8	4400:All	No
<b>Level of Service Determination (if not F)</b>					<b>Level of Service Determination (if not F)</b>				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> = 21.6 (pc/mi/ln) LOS = C (Exhibit 13-2)				

<b>RAMPS AND RAMP JUNCTIONS WORKSHEET</b>										
<b>General Information</b>					<b>Site Information</b>					
Analyst	AL				Freeway/Dir of Travel	I-75 EB				
Agency or Company	AIM ENGINEERING				Junction	SR 29 EB ON				
Date Performed	3/16/2012				Jurisdiction					
Analysis Time Period	PM				Analysis Year	2019 EVERGLADES				
Project Description										
<b>Inputs</b>										
Upstream Adj Ramp	Number of Lanes, N				2 ✓		Downstream Adj Ramp			
<input type="checkbox"/> Yes <input type="checkbox"/> On	Acceleration Lane Length, L <sub>A</sub>				560		<input type="checkbox"/> Yes <input type="checkbox"/> On			
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	Deceleration Lane Length L <sub>D</sub>						<input checked="" type="checkbox"/> No <input type="checkbox"/> Off			
L <sub>up</sub> = ft	Freeway Volume, V <sub>F</sub>				1317 ✓		L <sub>down</sub> = ft			
V <sub>u</sub> = veh/h	Ramp Volume, V <sub>R</sub>				201 ✓		V <sub>D</sub> = veh/h			
	Freeway Free-Flow Speed, S <sub>FF</sub>				70.0 ✓					
	Ramp Free-Flow Speed, S <sub>FR</sub>				35.0					
<b>Conversion to pc/h Under Base Conditions</b>										
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f <sub>HV</sub>	f <sub>p</sub>	v = V/PHF x f <sub>HV</sub> x f <sub>p</sub>		
Freeway	1317	0.90 ✓	Level	6	0	0.971	0.90 ✓	1675		
Ramp	201	0.90 ✓	Level	22	0	0.901	0.90	275		
UpStream										
DownStream										
<b>Merge Areas</b>					<b>Diverge Areas</b>					
<b>Estimation of v<sub>12</sub></b>					<b>Estimation of v<sub>12</sub></b>					
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L <sub>EQ</sub> = P <sub>FM</sub> = 1.000 using Equation (Exhibit 13-6) V <sub>12</sub> = 1675 pc/h V <sub>3</sub> or V <sub>av34</sub> = 0 pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L <sub>EQ</sub> = P <sub>FD</sub> = using Equation (Exhibit 13-7) V <sub>12</sub> = pc/h V <sub>3</sub> or V <sub>av34</sub> = pc/h (Equation 13-14 or 13-17) Is V <sub>3</sub> or V <sub>av34</sub> > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V <sub>3</sub> or V <sub>av34</sub> > 1.5 * V <sub>12</sub> /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V <sub>12a</sub> = pc/h (Equation 13-16, 13-18, or 13-19)					
<b>Capacity Checks</b>					<b>Capacity Checks</b>					
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?	
V <sub>FO</sub>	1950	Exhibit 13-8		No	V <sub>F</sub>		Exhibit 13-8			
					V <sub>FO</sub> = V <sub>F</sub> - V <sub>R</sub>		Exhibit 13-8			
					V <sub>R</sub>		Exhibit 13-10			
<b>Flow Entering Merge Influence Area</b>					<b>Flow Entering Diverge Influence Area</b>					
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?	
V <sub>R12</sub>	1950	Exhibit 13-8		No	V <sub>12</sub>		Exhibit 13-8			
<b>Level of Service Determination (if not F)</b>					<b>Level of Service Determination (if not F)</b>					
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D <sub>R</sub> = 17.0 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D <sub>R</sub> = (pc/mi/ln) LOS = (Exhibit 13-2)					